

NEW!



**SoloTech™ 10 Hose Pump**

- Max flow: 0.5 gpm (1.9 lpm)
- 10 mm hose



**SoloTech™ 23 Hose Pump**

- Max flow: 5.0 gpm (18.9 lpm)
- 23 mm hose



**SoloTech™ 26 Hose Pump**

- Max flow: 10 gpm (37.8 lpm)
- 26 mm hose



**SoloTech™ 30 Hose Pump**

- Max flow: 16.0 gpm (60.5 lpm)
- 30 mm hose



**Husky™ 1050e**

- 1 in (25.4 mm) connection
- Max flow: 42 gpm (159 lpm)
- Aluminum, polypropylene, stainless steel



**ChemSafe™ 205**

- 1/4 in (6.3 mm) connection
- Max flow: 3.7 gpm (14 lpm)



**ChemSafe™ 307**

- 3/8 in (9.4 mm) connection
- Max flow: 6.7 gpm (25 lpm)



**ChemSafe™ 515**

- 1/2 in (12.7 mm) connection
- Max flow: 16 gpm (60.6 lpm)



**ChemSafe™ 1040**

- 1 in (25.4 mm) connection
- Max flow: 38.8 gpm (146 lpm)



**ChemSafe™ 1590**

- 1-1/2 in (38.1 mm) connection
- Max flow: 99.5 gpm (376 lpm)



**Husky™ 205**

- 1/4 in (6.3 mm) connection
- Max flow: 5 gpm (19 lpm)
- Polypropylene, acetal, PVDF



**Husky™ 307**

- 3/8 in (9.4 mm) connection
- Max flow: 7 gpm (26 lpm)
- Polypropylene, acetal



**Husky™ 515**

- 1/2 in (12.7 mm) connection
- Max flow: 15 gpm (57 lpm)
- Polypropylene, acetal, PVDF



**Husky™ 716**

- 3/4 in (19.1 mm) connection
- Max flow: 16 gpm (61 lpm)
- Aluminum, SST



**Husky™ 1050**

- 1 in (25.4 mm) connection
- Max flow: 50 gpm (189 lpm)
- Aluminum, polypropylene, conductive polypropylene, PVDF, SST, hastelloy



**Husky™ 1050HP**

- 1 in (25.4 mm) connection
- Max flow: 50 gpm (189 lpm)
- Aluminum and SST



**Husky™ 1590**

- 1-1/2 in (38.1 mm) connection
- Max flow: 90 gpm (340 lpm)
- Polypropylene, aluminum, SST



### Husky 15120

- 1-1/2 in (38.1 mm) connection
- Max flow: 120 gpm (454 lpm)
- Polypropylene, PVDF



### Husky 2150

- 2 in (50.8 mm) connection
- Max flow: 150 gpm (568 lpm)
- Polypropylene, aluminum, SST, iron



### Husky 2200

- 2 in (50.8 mm) connection
- Max flow: 200 gpm (757 lpm)
- Polypropylene, PVDF



### Husky 3300

- 3 in (76.2 mm) connection
- Max flow: 300 gpm (1135 lpm)
- Polypropylene, aluminum, SST



### Husky Dispense System

- For 55 gallon (200 l) drums
- Full-width mixing provides color and material consistency throughout the drum



### Husky 515 Transfer Pump

- 1/2 in (12.7 mm) connection
- Max flow: 12 gpm (45 lpm)
- Polypropylene, acetal, PVDF



### Husky 716 Transfer Pump

- 3/4 in (19.1 mm) connection
- Max flow: 14 gpm (52 lpm)
- Aluminum, stainless steel



### 1:1 Fast-Flo®

- Max flow: 5 gpm (19 lpm)
- UL options available



### Husky Twistork Agitator

- Available with acetal or polypropylene
- Husky 515 diaphragm pump
- Mix paint, resins, urethanes, epoxies and latex materials up to 1000 cps



### Priming Piston Ink Pump

- Enclosed, dual seal wet cup for longer seal life
- Runaway control with optional DataTrak™



### Hydraulic Ink Pump

- Up to 3 times more efficient than pneumatic pumps
- Typical applications:
  - Letterpress inks
  - Lithographic inks



### Hydra-Clean® Pressure Washers

- High pressure cleaning and sanitizing
- Air-operated and hydraulic for hazardous or confined areas
- 10:1, 12:1, 23:1, 30:1 or 45:1 ratio options
- Available in wall, cart or drum mount packages



All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Visit us at [www.graco.com/process](http://www.graco.com/process) for product information or to request a demo.

