




EP™ Pour Gun

Next Generation Polyurethane Mixhead



Innovative air-powered pour gun simplifies mixhead rebuilds

- Includes rebuild kit for quick, easy maintenance
- Offers both manual and automated application modes
- For open pour applications and closed-mold injection
- Mechanically self-cleaning - eliminates costly solvent flushing
- Provides flow rates of 0.45 to 22.7 kg/min (1 to 50 lb/min)

PROVEN QUALITY. LEADING TECHNOLOGY.

Graco EP Pour Gun

Economy and Performance

EP

The Graco EP™ Pour Gun is sure to change the way the industry thinks about mixheads. That's because it's engineered to be reliable, light, versatile – with features and technology that reduce your cost of ownership in the long run.

Low initial investment

- Designed to perform like a hydraulic mixing head, without the power pack, therefore lowering your initial investment

Easy, do-it-yourself mixhead rebuilds save money

- Lower capital outlay and rebuild costs
- Updated technology allows for on-site rebuilds
- Reduces downtime
- Eliminates expense of backup mixheads

Flexible – handles multiple materials

- Processes both rigid and flexible polyurethanes
- Handles filled materials

Accurate, on-ratio dispensing

- Maintains accurate mix ratio – without the need for circulation in the head of the gun


Lightweight, great performance

- Responsive trigger delivers repeatable and accurate shots
- Weighs 2.9 to 3.4 kg
- Manual and automated capabilities

Compatible with multiple proportioners

- Graco HFR Metering System™
- Reactor® IPH-25 and IPH-40

Easy Mixhead Rebuilds



Orifice and needle design adds flexibility

- Easily adjusted to deliver the exact material mix for your process
- Provides wide range of flow rates – up to 22.7 kg/min (50 lb/min)

Powerful pneumatic design improves uptime

- Reduces sticking of the purge rod

Dual piston technology

- Reduces system costs by eliminating mixhead hydraulic power pack



Purge rod prevents sticking

- Lubricated purge rod reduces material sticking
- More uptime, better reliability
- Eliminates costly solvent flushing

Long-lasting impinger inserts

- Durable stainless steel impinger inserts for less maintenance
- Multiple flow rate and ratios – 1:1 to greater than 5:1
- 16 sizes available for various materials



Technical Specifications

EP POUR GUN

Flow rates	0.45 kg/min (1lb/min)
.....	up to 22.7 kg/min (50 lb/min)
Max. fluid working pressure.....	207 bar (20.7 MPa, 3000 psi)
Min. air inlet pressure	5.5 bar (0.55 MPa, 80 psi)
Max. air inlet pressure	6.9 bar (0.69 MPa, 100 psi)
Max. fluid temperature	82°C (180°F)
Air inlet size	1/4 npt quick disconnect nipple
A component inlet size	-5 JIC, 1/2 - 20 UNF
B component inlet size	-6 JIC, 9/16 - 18 UNF

Dimensions

With handle	274 x 79 x 297 mm
Without handle	274 x 79 x 155 mm

Weight

With handle	3.4 kg
Without handle	2.9 kg

Materials of construction	Aluminum, stainless steel, acetal,
.....	chemically-resistant o-rings,
.....	carbon steel, fluoroelastomer o-rings

Wetted parts	Aluminum, stainless steel, acetal,
.....	chemically-resistant o-rings

Manual	313872
--------------	--------



Ordering Information

GRACO EP250 POUR GUN

257999	Handheld gun with 6.35 mm (0.250 in) purge rod diameter and 0.79 mm (0.031 in) orifice size
24C932	Auto gun with 6.35 mm (0.250 in) purge rod diameter and 0.79 mm (0.031 in) orifice size
24D680	Fluid Housing Kit, 6.35 mm (0.250 in)

GRACO EP375 POUR GUN

24C933	Handheld gun with 9.53 mm (0.375 in) purge rod diameter and 1.2 mm (0.047 in) orifice size
24C934	Auto gun with 9.53 mm (0.375 in) purge rod diameter and 1.2 mm (0.047 in) orifice size
24D681	Fluid Housing Kit, 9.53 mm (0.375 in)

GRACO N.V. Industrierrein Oude Bunders
 Slakweidestraat 31 • B-3630 Maasmechelen
 Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777
 E-mail: info@graco.be • http://www.graco.com

©2010 Graco Inc. Form No. 340469E (rev. A) 05/10 Printed in Europe.
 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.