

Abrasion Resistant

Air-Operated Double Diaphragm Pumps



Graco® diaphragm pumps keep working through the toughest drilling applications

- Full line of abrasion-resistant aluminum pumps in 1 in (25 mm), 1.5 in (38 mm), 2 in (51 mm) and 3 in (76 mm) sizes
- Husky abrasion-resistant pumps move up to 300 gallons per minute (1135 lpm)
- Rugged construction for reliable performance and long life

Ordering Information

Husky 1050

Part No. (npt)	Size	Seat	Ball	Diaphragm
647666	1 in (25 mm)	TPE	Acetal	TPE
647040	1 in (25 mm)	Geolast	Geolast	Geolast
647025	1 in (25 mm)	Stainless Steel	Geolast	Geolast

Husky 1590

Part No. (npt)	Size	Seat	Ball	Diaphragm
DB3525	1.5 in (38 mm)	TPE	Acetal	TPE
DB3GGG	1.5 in (38 mm)	Geolast	Geolast	Geolast
DB33GG	1.5 in (38 mm)	Stainless Steel	Geolast	Geolast

Husky 2150

Part No. (npt)	Size	Seat	Ball	Diaphragm
DF3525	2 in (51 mm)	TPE	Acetal	TPE
DF3GGG	2 in (51 mm)	Geolast	Geolast	Geolast
DF33GG	2 in (51 mm)	Stainless Steel	Geolast	Geolast

Husky 3300

Part No. (npt)	Size	Seat	Ball	Diaphragm
652002	3 in (76 mm)	TPE	Acetal	TPE
652046	3 in (76 mm)	Geolast	Geolast	Geolast
652018	3 in (76 mm)	Stainless Steel	Geolast	Geolast

Geolast: Ideal for drilling applications. Superior abrasion resistance for non-solvent based material.

TPE: Excellent abrasion resistance for non-solvent-based material.

Acetal: Excellent for fatigue and abrasion resistance.

 ${\it Stainless \ Steel:}\ Greatest\ chemical\ compatibility\ and\ abrasion\ resistance.$



1 inch (25 mm) 1050 Diaphragm Pump



1.5 inch (38 mm) 1590 Diaphragm Pump



2 inch (51 mm) 2150 Diaphragm Pump



3300 Diaphragm Pump

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration. 877.84GRACO (1-877-844-7226) or visit us at www.graco.com.

