



# Husky™ 1050 Pumps

A Complete Family of 1 inch (25.4 mm)  
Air-Operated Double Diaphragm Pumps



There are  
**NO EQUALS**

- **30%** more efficient than the market leaders
- **20%** increase in fluid flow compared to the Husky 1040
- Up to **5 times** longer diaphragm life compared to other diaphragm pumps in its class
- Expanded material offering to handle **endless applications**

PROVEN QUALITY. LEADING TECHNOLOGY.

# HUSKY 1050 FAMILY

## No Limits. No Equals. No Problem.

At Graco, there are no limits when it comes to designing pumps that exceed your expectations.

That's why we're expanding our pump line.

## What makes these Husky Pumps among the Best in the Industry?

### Efficiency

30% more efficient than the industry leaders.

### Performance

Delivers material up to 50 gpm (189 lpm). That's a 20% increase in flow\*!

### Engineering

Diaphragms last 5 times longer than others in its class\*.

Buy a Husky 1050 pump today and you'll quickly see why there are NO EQUALS!

\*When compared to the Husky 1040.



Aluminum



Polypropylene



Stainless Steel



PVDF

**SIX MATERIALS. ENDLESS APPLICATIONS.**



### Modular Air Valve

Stall-free, low pulsation operation provides smooth and rapid changeover

### One-Piece Center Section

Eliminates air leaks for more efficient operation

### Longer Diaphragm Life

Up to 5x longer diaphragm life for less maintenance and downtime

### Optional Features

#### DataTrak™

- Runaway protection
- Tracks material usage

#### Pulse Output

- Cycle count capability



### Four Bolt Joint Design

Bolted design provides even sealing pressure for leak-free operation

### Multiple Ports

Increased number of ports for installation flexibility



Conductive Polypropylene



Hastelloy

## Find the Right Pump for your Application

Graco is making it easy to select a pump that's right for your application.

To order a Husky 1050, use the online selector tool at [www.gracohusky.com](http://www.gracohusky.com) or contact your distributor.



Example of Product Selector Tool on [www.gracohusky.com](http://www.gracohusky.com).

### WHAT'S NEXT?

Watch for the next pump in Graco's new series of air-operated double diaphragm pumps.

# Husky 1050 Technical Specifications

Maximum fluid working pressure.....	125 psi (8.6 bar, 0.86 MPa)
Air pressure operating range.....	20-125 psi (1.4-8.6 bar, 0.14-0.86 MPa)
Maximum air consumption.....	67 scfm
Air consumption at 70 psi (4.8 bar, 0.48 MPa), 20 gpm (76 lpm) .....	25 scfm
Maximum free-flow delivery .....	50 gpm (189 lpm)
Maximum pump speed .....	280 cpm
Fluid displacement per cycle.....	0.17 gal (0.64 liters)
Maximum suction lift .....	16 ft (4.9 m) dry, 29 ft (8.8 m) wet
Maximum size pumpable solids .....	1/8 in (3.2 mm)
Sound Power*	
at 70 psi (4.8 bar, 0.48 MPa) and 50 cpm.....	78 dBa
at 100 psi (7.0 bar, 0.7 MPa) and full flow .....	90 dBa
Sound Pressure**	
at 70 psi (4.8 bar, 0.48 MPa) and 50 cpm.....	84 dBa
at 100 psi (7.0 bar, 0.7 MPa) and full flow .....	96 dBa
Air inlet size .....	1/2 npt(f)
Fluid inlet size	
Aluminum (1050A).....	1 in npt(f) or 1 in bspt
Plastic (1050P, 1050C and 1050F) .....	1 in raised face ANSI/DIN flange
Stainless Steel (1050S and 1050H) .....	1 in npt(f) or 1 in bspt
Fluid outlet size	
Aluminum (1050A).....	1 in npt(f) or 1 in bspt
Plastic (1050P, 1050C and 1050F) .....	1 in raised face ANSI/DIN flange
Stainless Steel (1050S and 1050H) .....	1 in npt(f) or 1 in bspt
Weight	
Aluminum (1050A).....	23 lb (10.5 kg)
Plastic (1050P and 1050C) .....	18 lb (8.2 kg)
PVDF (1050F).....	26 lb (11.8 kg)
Stainless Steel (1050S)	
with conductive polypropylene center.....	37 lb (16.8 kg)
with polypropylene center.....	37 lb (16.8 kg)
with aluminum center .....	41 lb (18.6 kg)
Hastelloy (1050H) .....	41 lb (18.6 kg)
Wetted parts	
Aluminum (1050A).....	aluminum and material(s) chosen for seat, ball, and diaphragm options
Polypropylene (1050P and 1050C) .....	polypropylene and material(s) chosen for seat, ball, and diaphragm options
PVDF (1050F).....	PVDF and material(s) chosen for seat, ball, and diaphragm options
Stainless Steel (1050S) .....	stainless steel and material(s) chosen for seat, ball, and diaphragm options
Hastelloy (1050H) .....	hastelloy, stainless steel and material(s) chosen for seat, ball, and diaphragm options
Non-wetted external parts	
Aluminum (1050A).....	Center aluminum Bolts coated carbon steel
Plastic (1050P, 1050C and 1050F) .....	polypropylene stainless steel
Stainless Steel (1050S) .....	polypropylene stainless steel
Stainless Steel (1050S).....	aluminum stainless steel
Hastelloy (1050H) .....	polypropylene stainless steel
Operational Manual.....	312877
Repair/Parts Manual .....	313435

\* Sound power measured per ISO-9614-2.

\*\* Sound pressure was tested 3.28 ft (1 m) from equipment.

HUSKY MODELS










**205**  
1/4 in (6.3 mm)  
5 gpm (19 lpm)

**307**  
3/8 in (9.4 mm)  
7 gpm (26 lpm)

**515**  
1/2 in (12.7 mm) or  
3/4 in (19.1 mm)  
15 gpm (57 lpm)

**716**  
3/4 in (19.1 mm)  
16 gpm (61 lpm)

**1050**  
1 in (25.4 mm)  
50 gpm (189 lpm)

**1590**  
1-1/2 in (38.1 mm)  
90 gpm (340 lpm)

**2150**  
2 in (50.8 mm)  
150 gpm (568 lpm)

**3275**  
3 in (76.2 mm)  
275 gpm (1041 lpm)

FEATURED PUMP

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.  
**877.84GRACO** (1-877-844-7226) or visit us at [www.graco.com/process](http://www.graco.com/process).

©2010 Graco Inc. 344801 Rev. B 6/10 Printed in the U.S.A.  
 All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

