


SaniForce™

Sanitary Pumping Solutions: diaphragm pumps, piston pumps, drum and bin unloaders for sanitary applications



Air-Operated Double Diaphragm Pumps

- Maximum flow rates to 567 lpm (150 gpm)
- Tri-clamp connections
- Fluid pressure up to 8.4 bar (0.84 MPa, 120 psi)
- Durable, lube-free non-sticking air valve



3A and High Sanitation Diaphragm Pumps

- Maximum flow rates to 567 lpm (150 gpm)
- Fluid pressure up to 8.4 bar (0.84 MPa, 120 psi)
- Quick knockdown design for easy cleaning and draining
- Durable, lube-free non-sticking air valve
- Interchangeable flapper and ball checks
- Leak detection available



SaniForce Elevator

- Fluid transfer and supply of low to medium viscosity fluids
- Flow rates ranging from 5.7 to 53 lpm (1.5 to 14 gpm)
- Mobile and stationary options available



Bin Evacuation Systems™ (BES)

- Evacuate materials from 1.135 l (300 gallon) containers without adding water
- Inflatable wiper seals for increased efficiency and faster change-out of bins
- Available with two sanitary diaphragm pumps or up to four sanitary piston pumps
- Pneumatic or electronic control options



Piston Pumps

- Fluid transfer and supply of low to medium viscosity fluids
- Flow rates ranging from 5.7 to 53 lpm (1.5 to 14 gpm)
- Double-ball and priming piston designs



Drum Unloaders

- Unload materials from straight-sided or tapered drums
- Inflatable wiper seals for increased efficiency and faster change-out of drums
- Liner guard to prevent bags from entering pump
- Sanitary flange clamps for quick disassembly

SaniForce™ Pumping Solutions for sanitary applications

Graco pumps are a **DEPENDABLE, EASY-TO-SERVICE** solution for CIP applications.



Husky™ 205

- 6.3 mm (1/4 in) connection
- Max flow: 19 lpm (5 gpm)
- Polypropylene, PVDF



Husky 307

- 9.4 mm (3/8 in) connection
- Max flow: 26 lpm (7 gpm)
- Polypropylene



Husky 515

- 12.7 mm (1/2 in) connection
- Max flow: 57 lpm (15 gpm)
- Polypropylene, PVDF



Husky 1050

- 25.4 mm (1 in) connection
- Max flow: 189 lpm (50 gpm)
- Polypropylene, PVDF



Husky 15120

- 38.1 mm (1-1/2 in) connection
- Max flow: 38.1 mm (120 gpm)
- Polypropylene, PVDF



Husky 2200

- 50.8 mm (2 in) connection
- Max flow: 757 lpm (200 gpm)
- Polypropylene, PVDF



Hydra-Clean™

- High pressure cleaning and sanitizing
- Air-operated and hydraulic for hazardous or confined areas
10:1, 12:1, 23:1, 30:1 or 40:1 ratio options
- Available in wall, cart or drum mount packages



All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco is certified ISO 9001.

GRACO DISTRIBUTION BVBA Industrieterrein Oude Bunders • Slakweidestraat 31 • B-3630 Maasmechelen
Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777 • <http://www.graco.com>

©2014 Graco Distribution BVBA 345067ENEU Rev. A 04/17 Printed in Europe.
All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

