

# **Cultured Dairy Applications**

**Graco Sanitary Solutions** 





### SaniForce™ Piston Pumps and Unloaders

for moving and unloading semi-viscous to viscous materials

#### **SaniForce Piston Pumps**

- Perfect for fluid transfer of semi-viscous to viscous materials
- Quick knockdown design
- On-demand pumps constructed of 300 series stainless steel

#### **Popular Models**

24E840 6:1 drum length pump, 36,6 mm (1,44 in) inlet, buna,

nylon, nitrile packings

24E839 6:1 drum length pump, 36,6 mm (1,44 in) inlet,

PTFE packings

#### **SaniForce Drum and Bin Unloaders**

- Deliver fast and easy drum and bin evacuations
- Designed with inflatable wiper seals for increased efficiency and faster change-out of drums
- Available in diaphragm and piston pump configurations
- Safe method of transfer as the drum stays on the floor and doesn't need to be raised to dump the material.
- Clean way of working, the surroundings of the drum unloader stays clean.

#### **Popular Models**

24D714 SaniForce 5:1 priming piston pump with inflatable

wiper seal

24D936 SaniForce 3150 HS diaphragm pump with inflatable

wiper seal

BESA7C Two 5:1 double ball pumps, inflatable wiper seal

will accomodate 1135 I (300 gal) plywood bin









## SaniForce™ 1590 and 3150 High Sanitation

for blending and packing materials

#### SaniForce 1590 HS and 3150 HS with 3A Certification

- Models have flow rates ranging from 340-568 l/min (90-150 gpm)
- Easy to clean with its quick knockdown design
- High sanitation surface finish at 32 Ra

#### **Popular Models**

SBBAAA Saniforce 1590 HS - 50,8 mm (2 in) inlet/outlet with PTFE

balls and EPDM overmolded diaphragms

SA33A1 Saniforce 3150 HS - 76,2 mm (3 in) inlet/outlet with PTFE

balls and EPDM/PTFE overmolded diaphragms



SaniForce 3150 HS



SaniForce 3150 3A



All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco is certified ISO 9001.

