



Graco Sanitary Solutions





SaniForce™ Diaphragm Pumps

for pre- and post-pasturization material transfer

SaniForce 1040, 1590 and 2150 Diaphragm Pumps

- Wide range of food-grade diaphragms available including Santoprene, PTFE and EDPM/PTFE overmolded
- Flow rates ranging from 151-568 l/min (40-150 gpm)

Popular Models

FD1113 SaniForce 1040 - 38 mm (1,5 in) inlet/outlet with SST seats, PTFE balls and overmolded diaphragms

FD2113 SaniForce 1590 - 50,8 mm (2,0 in) inlet/outlet with SST seats, PTFE balls and overmolded diaphragms

FD3113 SaniForce 2150 - 63,5 mm (2,5 in) inlet/outlet with SST seats, PTFE balls and overmolded diaphragms



SaniForce 1040 38 mm (1,5 in)



SaniForce 1590 50,8 mm (2 in)



SaniForce 2150 63,5 mm (2,5 in)

SaniForce 1590 HS and 3150 HS Diaphragm Pumps

- Easy to clean, quick knockdown design
- Flow rates ranging from 340-568 l/min (90-150 gpm)
- High sanitation surface finish at 32 Ra

Popular Models

SB3AA1 SaniForce 3150 - 76 mm (3 in) inlet/outlet with overmolded PTFE diaphragms and PTFE balls

SA33A1 SaniForce 3150 - 76 mm (3 in) inlet/outlet with overmolded EPDM/PTFE diaphragms and PTFE balls



SaniForce 1590 HS 50,8 mm (2 in)



SaniForce 3150 HS 76 mm (3 in)



SaniForce™ Piston Pumps

for applications needing low flow rates

SaniForce Piston Pumps

- Ideal for fluid transfer of semi-viscous to viscous materials
- Quick knockdown design

Popular Model

24E840

6:1 drum length pump, 36,6 mm (1,44 in) inlet, buna, nylon, nitrile packings

SaniForce Drum Unloaders

- Ideal for unloading medium to high viscosity purees
- Unload 208 I (55 gal) drums with rates up to 378,5 I/min (100 gpm)
- Quick disconnect for fast and easy cleaning
- Safe method of transfer as the drum stays on the floor and doesn't need to be raised to dump the material
- Clean way of working, the surroundings of the drum unloader stays clean

Popular Model

24D714 SaniForce 5:1 piston pump drum unloader







All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice

Graco is certified ISO 9001.

