

Wine Applications

Graco Sanitary Solutions





SaniForce™ Diaphragm Pumps

for barrel-to-barrel transfer and pump-over

SaniForce 1040, 1590 and 2150 Double Diaphragm Pumps

- Ideal for food-related applications requiring maximum portability
- Models with flow rates ranges from 151-567 I/min (40-150 gpm)

Popular Models for Barrel-to-Barrel Transfer

FD1111 SaniForce 1040 - 38 mm (1,5 in) flange connection SST seats, PTFE balls and diaphragms
Maximum flow 151 I/min (40 gpm)

FD1113 SaniForce 1040 - 38 mm (1,5 in) flange connection SST seats, PTFE balls and overmolded diaphragms Maximum flow 151 I/min (40 gpm)

Popular Models for Pump-Over

FD2113 SaniForce 1590 - 50,8 mm (2 in) flange connection SST seats, PTFE balls and overmolded diaphragms Maximum flow 340 l/min (90 gpm)

FD3113 SaniForce 2150 - 63,5 mm (2,5 in) flange connection SST seats, PTFE balls and overmolded diaphragms Maximum flow 567 l/min (150 gpm)



SaniForce 1040 38 mm (1,5 in)



SaniForce 1590 50,8 mm (2 in)



SaniForce 2150 63,5 mm (2,5 in)



Husky™ Diaphragm Pumps

for top off

Husky 515 Polypropylene Diaphragm Pumps

- Easy-to-service air valve and ball check
- Reliable air valve for years of dependable performance

Popular Model

D52966

Husky polypropylene 515, 12,7 mm (1/2 in) connection size Polypropylene seats, santoprene balls and diaphragms Maximum flow 56 l/min (15 gpm)



Husky 515, Poly 12.7 mm (1/2 in)



All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco is certified ISO 9001.

