G3[™] Electric Lubrication Pump GRACO

For Series Progressive and Injector-based Systems

Versatile Design Helps Solve Today's Lubrication Challenges

Temperature changes, changing grease types and challenging installation requirements are no problem for the G3 electric lubrication pump. With its flexible design, including five reservoir sizes, three controller options, three power types and an adjustable pump element, the G3 is a rugged, cost-effective pump designed to serve multiple markets and applications.



If You're Not Using **Graco G3**[™] Pumps, You're Not **Maximizing** Your **Profits**.



Rigorously tested to pass Graco specifications and earn these approvals we'd love to have yours, too.



Contact Us Today!

To receive product information or to speak with a Graco representative, call 800-533-9655 or for a complete list of G3 Pumps and configurations visit us online at www.graco.com.

Versatile Design Helps Solve Today's Lubrication Challenges.

Why G3[™] is Better

Two in One Design Does More!

G3's flexible design works with injector-based and series progressive systems. A cost-effective pump designed to serve multiple markets and applications.

Options that Fit Your Business

Three controllers to choose from with multiple zone and feedback options. Includes one adjustable pump element–standard, plus room for two more. Multiple reservoir choices and more! The ultimate in flexibility–for a high value, custom fit on your application.

Built-in Tools to Help You Succeed

Work faster and smarter with Graco's exclusive Data Management System (DMS[™]). Find out exactly how your lubrication system is performing and how well it's lubricated. Tracks history, provides data protection, upload or download data using a simple USB flash drive.

World Wide Support with Experienced Professionals

Graco wants to help you become more successful. Our staff of professional engineers, designers, field experts and customer service representatives are at your service. We invite you to call on us to partner in your next project.

Extend Machinery Life, Reduce Operating Costs and Increase Productivity with a Graco G3[™] Today!

Take a Look Inside – We Think You'll Like What You See.

Designed from the inside-out for longer lasting performance and reliability. G3 meets changing temperatures, challenging installation requirements and changing grease types head-on. Graco's newest electric pump delivers high performance results in real world application conditions.



Advanced Flow Dynamics Specially contoured base funnels grease directly to the pump inlet to significantly reduce stagnant flow areas where soaps and grease fillers can accumulate.



Adjustable Stroke Pump With G3, adjustability comes standard! Eliminate the need to purchase additional fixed output elements or high-priced adjustable elements.



Load Minimizing Drive Each G3 piston pump element is offset from the main motor shaft resulting in less stress on the motor and internal components.

Versatile, Hard-working Pump

Designed for You to Succeed

Two Reservoir Types

Stirring paddle with wiper arm to keep material from separating. Follower plate available for extreme angle installations.

Power Choices

Connect to DC (12 or 24V) and AC (90-240V) power sources with CPC or DIN-style connectors for easy, no hassle installations.

Vent Valve Output

Combine Max controller with a vent valve for injectorbased systems.

Four Controller Options

Choose from Standard, Pro, SP and Max controller options – buy only what you need for your application.



Data Management System (DMS)

- Simple data transfer to your PC via USB flash drive for further analysis using Excel® or Notepad®
- Provides performance history for lube system events, such as cycle detection, error logs and allows a quick check of lubrication performance to meet your system requirements
- Preferred lube cycle program can be stored and transferred to other G3 pumps in your fleet for quick and accurate repeatability
- Provides you the comfort and security in knowing your pump is being properly maintained and your lube system is protecting your valuable asset



Multiple Reservoir Sizes

Choice of 2, 4, 8, 12 or 16 liter U.V. resistant, high-impact reservoirs for oil and grease to meet the needs of your equipment.

Three Pump Elements

G3 comes standard with one adjustable pump element installed – add up to two more for higher output on large projects.

Multiple Cycle and Pressure Inputs

Mix and match up to three cycle and pressure switches for custom installations and feedback.

Machine Count Input

Machine count input to manage equipment with unpredictable lubrication requirements.

Auto-Fill Shutoff (AFSO)

- Available on G3 Standard, Pro and Max
- Eliminates over- or under-filling
- Completely fill the reservoir every time while avoiding costly spills
- Does not require power to operate
- Complies with stringent mining regulations where a system must be powered down during fluid refilling
- Compatible with fast-fill-equipped lubrication trucks
- Reservoir Full Visual Indication
- Valve Plate activates a poppet valve, which cuts off grease flow into the reservoir

Excel and Notepad are registered trademarks of Microsoft Corporation in the United States and other countries.

Control for Your Business

Standard, Pro, SP and Max

Choose the level of control you need for your series progressive or injector based applications.

G3 Standard

- No internal controller use with separate or existing machine control for a low cost solution
- Capable of sending a low level signal to your external controller or PLC



G3 Pro

- Built-in controller with selectable pump on/pump off timer
- Low level indicator provides low warning and shut-down alarm
- Manual run initiates lube cycle on-demand (remote option also available)
- Password protection safeguards settings
- Pre-lube function can initiate lube cycle on start-up

G3 SP

- Simple programming and valuable system feedback
- Low level indicator provides low warning and shut-down alarm



- Only programming requirements are number of cycles and off time between lube events
- Manual run initiates lube cycle on-demand (remote option also available)
- · Password protection safeguards settings
- Pre-lube function can initiate lube cycle on start-up

Technical Specifications

5,100 psi (352 bar)
12 VDC, 24 VDC, 90-240 VAC
-40 to 158° F (-40 to 70° C) depending on lubricant used
2, 4, 8, 12 or 16 liter
0.12 in ³ , 0.18 in ³ , 0.25 in ³ (2 cm ³ , 3 cm ³ , 4 cm ³)
Oil or Grease, up to NLGI #2
CE, ETL*, IP69K *Conforms to UL 73, certified to CSA 22.2 No. 68-09
Standard - 332291 / Pro - 332298 SP - 3A4676 / Max - 332305

G3 Max

- Built-in controller with selectable
 pump on/pump off timer
- Low level indicator provides low warning and shut-down alarm
- Manual run initiates lube cycle on-demand (remote option also available)
- Password protection safeguards
- Pre-lube function can initiate lube cycle on start-up
- Up to three pressure or cycle switch inputs to ensure proper lubrication cycles
- Mix/match cycle and pressure switches for custom installations and feedback
- Machine count input ideally suited for inconsistently used equipment
- · Fault indication to external alarms
- Optional Data Management System[™] (DMS)

Check Out the Full-featured G3 Max OFF ON MM : SS HH : MM 4 0 1 2 3 1 Easy-to-read LED display Warning signal prior to (6)lube system shutdown (2) Clearly identified pump on/off indication 7 Low level indication 3 Monitoring of up to three 8 Password protected independent zones access to control 4 Programmable machine 9 Pre-lube capability count feature Easy-to-use (10)(5) Alarm signal of lube system navigation keys shutdown



AMERICAS

MINNESOTA

Worldwide Headquarters Graco Inc. 88-11th Avenue N.E. Minneapolis, MN 55413

MAILING ADDRESS P.O. Box 1441 Minneapolis, MN 55440-1441 Tel: 612-623-6000 <u>Fax: 612-623-6777</u>

EUROPE

BELGIUM Graco BVBA Industrieterrein-Oude Bunders Slakweidestraat 31 B-3630 Maasmechelen, Belgium Tel: 32 89 770 700 Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA Graco Australia Pty Ltd. Suite 17, 2 Enterprise Drive Bundoora, Victoria 3083 Australia Tel: 61 3 9468 8500 Fax: 61 3 9468 8599

CHINA

Graco Hong Kong Ltd. Shanghai Representative Office Building 7 1029 Zhongshan Road South, Huangpu District Shanghai, 200011 The People's Republic of China Tel: 86 21 649 50088 Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd. India Liaison Office Room 443, Level 4 Augusta Point, Golf Course Road Gurgaon, Haryana, India 122001 <u>Tel: 91 124</u> 435 4208 Fax: 91 124 435 4001

JAPAN

Graco K.K. 1-27-12 Hayabuchi Tsuzuki-ku Yokohama City, Japan 2240025 Tel: 81 45 593 7300 Fax: 81 45 593 7301

KOREA

Graco Korea Inc. Shinhan Bank Building 4th Floor #1599 Gwanyang-Dong, Dongan-Ku, Anyang-si, Korea 431-060 Tel: 82 31 476 9400 Fax: 82 31 476 9801


©2020 Graco Inc. 340574 Rev. F 3/20 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.



Graco's got you covered

Facilities Worldwide for Global Support





Quality First

At Graco we pride ourselves on providing best-in-class products. Engineered solutions are manufactured in our own facilities, with the highest standards in the industry. We provide you with world-class customer support and expertise to help solve your lubrication challenges.

Global Reach

Graco has facilities and distribution partners across the globe to provide you with the products and service *you* need, where *you* live. Plus, Graco has dedicated field experts in all areas of the world to support the products we sell.

Product Capabilities

Graco has a broad range of products to provide solutions that meet your needs. Our products are engineered and tested to perform in the harshest environments so you can be certain your equipment is protected and working at peak performance.

Contact us today!



Call **800-533-9655** to speak with a Graco representative, or visit **www.graco.com** for more information.