# **SDI15 In-Line Meter**

High-Pressure/High-Flow Meter for Accurately Recording Fluid Dispense



### Compact and Accurate, Suitable for In-line and End-of-line Applications

- Precise and repeatable measurement of dispenses with digital readout in .01 increments up to 999.99 gallons, quarts, pints or liters
- Rugged and robust meter with integrated electronics and large LC display
- Designed for indoor use and easily calibrated for a variety of fluid viscosities
- Energy efficient sleep mode allows batteries to last longer-powered by 2 AA alkaline batteries
- Flow rates from 0.1 to 14 gallons per minute (0.4–52 liters per minute)



Simple bolt-on meter-ideal for oil and anti-freeze applications that require high-pressure/high-flow.

## **Contact us today!**

Send an E-mail to info\_APLube@graco.com for product information or visit us at www.graco.com

Australia Office Tel: +61 3 9468 8500

India Office Tel: +91 124 435 4208

China Office Tel: +86 21 6495 0088

Japan Office Tel: +81 45 593 7300

Korea Office Tel: +82 31 476 9400

©2011 Graco Inc. 340513 Rev. A 05/2011 Printed in China.

All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in his document are based on the latest product information available at the time of publication. Graco reserves the right to mark changes at any time without notice.

# Dispense up to 14 gpm (52 lpm)

Fast and accurate fluid dispense makes recording and tracking fluid inventories simple. Account for all fluid dispenses—reduces inventory loss, increases profits.



#### Rugged SST Body

Remains corrosion-free in harsh environments for years of trouble-free service

#### Compact Design

Ideal for oil (petroleum and synthetic) and anti-freeze applications (only 5 in x 3 in)

#### Large LED Display

Intuitive controls are displayed for easy operation in all conditions

#### Two Recording Modes

Accurately records totals based on user needs—reset mode for single dispenses or non-reset mode for total meter life history

#### **Ordering Information**

247453 SDI15 in-line meter

#### **Technical Specifications**

Flow Range	0.1 to 14 gpm (0.4 to 52 lpm)
Maximum Fluid Working Pressure	1500 psi (103 bar)
Units of Measure	Quarts, pints, gallons, liters (comes set from factory in quarts)
Weight	1.8 lbs (0.82 kg)
Inlet	1/2 npt (f)
Outlet	1/2 npt (f)
Maximum Totalizer	99,999.99 gallons, quarts
Maximum Recorded Dispense	999.99 units
Operating Temperature	-4 °F to 122 °F (-20 °C to 50 °C)
Storage Temperature	-13 °F to 122 °F (-25 °C to 50 °C)
Battery	2 AA alkaline
Battery Life	6 to 12 months
Wetted Materials	SST, pbt/pc, nitrile rubber
Meter Pressure Loss	22 psi at 15 gpm with 10 weight oil @ 72 °F 2.2 bar at 57 lpm with 10 weight oil @ 22 °C
Accuracy	+/- 0.5%
Dimensions	5 in long x 3 in wide x 3 in deep (12.7 cm x 7.6 cm x 7.6 cm)
Warranty	1 year
Instruction Manual	313048