

FAST-BALL® 100 PUMP

Designed for Enhanced Quality, Durability and Reliability

When you purchase Graco, you expect the best. The fully redesigned Fast-Ball delivers unmatched Graco performance and operation. Its simple, easy-to-install design allows for efficient serviceability to minimize downtime and keep your operations running.

In-Line Design

• Means fewer parts for less pump wear

Double-Acting Pump

• Provides reliable fluid flow

Differential Air Motor

• Ensures smooth pump operation

5-Year Warranty

• Graco's quality guarantee and peace of mind

SPECIFICATIONS	Air Inlet Size	1/4 in NPT
	Air Operating Range	40-150 psi (2.8-10.3 bar)
	Compatible Material	Oil, Gear Lube, ATF
	Maximum Fluid Flow	12.5 gpm (47.3 lpm)
	Fluid Inlet Size	1 in NPT
	Fluid Outlet Size	3/4 in NPT
	Maximum Air Inlet Pressure	150 psi (10.3 bar)
	Maximum Continuous Cycle Rate	100 cpm
	Maximum Working Pressure	150 psi (10.3 bar)
	Power Type	Pneumatic
	Pump Ratio	1:1
	Sound Power Level	78 dB(A)
	Weight	6.3-9.8 lbs (2.9-4.4 kg)

FAST-BALL 100 PUMPS

PART NUMBER	DESCRIPTION
279035	Universal Length Pump
279036	Cut-to-Length PVC Downtube Pump
279037	55 Gallon Drum Length Pump



10-00

TYPICAL APPLICATIONS

- Fluid Transfer
- Specialty Fluid Dispenses
- Point of Use
- Mobile Fluid Carts

For more information, visit graco.com/vehicle-service.

©2023 Graco Inc. 353407 Rev. A 4/23 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. For more information on Graco's intellectual property, see www.graco.com/patent or www.graco.com/trademarks.