

GENUINE GRACO PARTS AND ACCESSORIES

Fluid Diaphragm Repair Kits 238747 and 17M565

Cartridge Repair Kits 238748, 248098, 258008, 24U712, and 17M566

For Stainless Steel, Waterbase-Compatible, High Pressure Fluid Pressure Regulators 238889, 238890, 238891, 238892, 238894, 243090, and 26A086



Important Safety Instructions

Read all warnings and instructions in manual 308647. Save those instructions.

406342G


EN

Kits 238747 and 17M565

Ref. No.	Part No.	Description	Qty.
1*		ACTUATOR	1
	26A091	ACTUATOR (for 17M565)	
7*		PLUNGER	1
12*		DIAPHRAGM, TPE	1
13*		DIAPHRAGM, PTFE	1
17	109213	O-RING, packing	1
19*		O-RING, packing	1

Kits 238748, 248098, 258008 and 17M566

Ref. No.	Part No.	Description	Qty.
3*	191577	NUT, spring retainer	1
	17M079	NUT, spring retainer (for 17M566)	
5*	191579	VALVE, housing, sst (for 238748, 248098, 17M566 and 24U712)	1
	15J924	VALVE, housing, sst (for 258008 only)	1
14*	191914	SEAT, valve	1
	16X783	SEAT, valve (for 24U712)	
	17M081	SEAT, valve (for 17M566)	
15*	113651	O-RING, packing	1
16*	112365	BALL, bearing (for 238748)	1
	15D092	BALL, bearing (for 248098 and 258008)	
	127363	BALL, bearing (for 24U712)	
	17M075	BALL, bearing (for 17M566)	
18*	107079	O-RING, packing	1
20*	109450	O-RING, packing	1
21*	111858	SPRING, compression	1
	17M078	SPRING, compression (for 17M566)	



- 1 Torque to 25 to 30 in-lb (2.8 to 3.4 N·m).
- 2 Torque to 140 to 160 in-lb (15.8 to 18.1 N·m).
- 3 Apply lithium-based grease when reassembling.
- 4 Torque to 30 to 35 ft-lb (40.7 to 47.5 N·m).