

XP-hf

Plural Component Sprayers for the Highest Demand Protective Coating Applications



Protective Coating Applications

Total Solution for High Output Applications

The XP-hf system combines the popular XP[™] Sprayers with the powerful XL[™] 10.000 air motor. Combining these two technologies, **you get more flow** - getting jobs done faster and with less wear and tear.

What an XP-hf Sprayer can do for you:



Increase Productivity & Labour Savings

With 60% more flow than the existing*
XP Sprayers and the ability to use larger tips, or run more than one gun off one system, you can get jobs done faster.

*Running at same cycle rate.



Save Time

Pre-wired packages with heaters and junction box means less hassle and faster set up time.



Easier to Service

The Xtreme[™] metering pumps with quick knock-down makes it easy to service; built-in fluid filter and spring loaded lower ball checks for crisp changeover.

The mechanically operated sprayer makes it easy to understand.



Improve Spray Pattern

Viscosity control with Viscon™ HF Fluid
Heaters improves spray pattern and
film thickness control. Viscon HF
heaters (5400 W) are 3 x less restrictive
than Viscon HP with removable,
cleanable aluminum core — making
it ideal for high demand applications.




High Demand Applications

XP-hf is designed with **more flow capacity**, making it ideal for high-output applications such as railcars, tank linings, marine coatings and much more. XP-hf meets your high production needs, so you get jobs done faster.







SECONDARY CONTAINMENT

Specifications

Graco Has You Covered

Flexible options for mix ratio, pressure and flow rate — choose the right system for the application. If you occasionally change materials, the Graco XP-hf Sprayer is the right choice for you. That's because you can change the ratio by simply changing out one or two pump lowers.





Available in two models:

	XP50-hf	XP70-hf				
Typical Materials	Medium to high solids coatings	High to 100% solids coatings				
Max Fluid Pressure (ratio dependant)	325 to 350 bar (4750 to 5000 psi)	490 to 500 bar (7100 to 7250 psi)				
Flow Rate at 40 cpm (approximate)	15 lpm (4 gpm)	11.5 lpm (3 gpm)				
Available Standard Mix Ratios	1:1 1.5:1 2:1 2.5:1 3:1 4:1	1:1 1.5:1 2:1 2.5:1 3:1 4:1				

The Largest, Most Powerful Air Motor Graco Has Ever Built

Unmatched icing performance, more power, easier troubleshooting and fewer parts - XL 10.000 air motor technology with 10.000 cc displacement - **Graco's largest air motor**.



• Exposed Poppet-Valves
Easy access for service
and troubleshooting.

 De-Ice Bleed Air Control Maintains performance during heavy icing conditions.

Manual Shuttle Override Button
 Allows manual changeover of air motor if main valve experiences ice buildup.

Simplified Valve Design

Fewer components for easier serviceability and hardly any pulsation or pattern fluctuation, even with multiple guns. Quiet operation, even compared to smaller motors.

External Pilot Lines Isolate lines from cold valve body. Eliminates non-restartable icing stalls.

A Closer Look at XP-hf

Graco XP-hf Powered by XL 10.000 Air Motor

Junction Box (Non-hazardous)





XL 10.000 Air Motor

 The high output, high efficiency 10.000 cc lets you use multiple guns with almost no perceivable pulsation

Material Hoppers

- 26 litre (7 gal) hoppers hold
 A and B components until it's time to spray
 - Optimised for direct pump feed

• Portable cart with tow handle fits through a 915 mm (36") doorway

Ordering Information

70:1

All packages include: XTR702 spray gun, 10.5 m (35 ft) hose, 500 bar (7250 psi) circulation manifold and standard mix manifold.

		CART	26 LITRE (7 GALLON) HOPPERS	SOLVENT PUMP	VISCON HF - HAZ LOC HEATERS (2)	VISCON HF - NON HAZ LOC HEATERS (2)	NON HAZ LOC JUNCTION BOX	VISCON HP - HAZ LOC HEATER (Hose)	VISCON HP - NON HAZ LOC HEATER (HOSO)	HEATED HOSE CIRC KIT	PRESSURE TRAK	A/B LOWER SIZES (cc)
	572100											145/145
	572101	•										145/145
(1:1 MIX RATIO)	572102	•	•									145/145
(RA	572103	•		•	•							145/145
Ž	572104	•	•	•	•							145/145
Ξ	572105	•	•	•		•	•					145/145
_	572106	•	•	•	•			•		•	•	145/145
	572107	•	•	•		•	•		•	•	•	145/145
	572150											145/97
	572151	•										145/97
(1.5:1 MIX RATIO)	572152	•	•									145/97
X R	572153	•		•	•							145/97
롣	572154	•	•	•	•							145/97
.5:1	572155	•	•	•		•	•					145/97
ב	572156	•	•	•	•			•		•	•	145/97
	572157	•	•	•		•	•		•	•	•	145/97
	572200											180/90
_	572201	•										180/90
(2:1 MIX RATIO)	572202	•	•									180/90
(RA	572203	•		•	•							180/90
Ê	572204	•	•	•	•							180/90
2:1	572205	•	•	•		•	•					180/90
_	572206	•	•	•	•			•		•	•	180/90
	572207	•	•	•		•	•		•	•	•	180/90

See manual #3A4381 for complete ordering information.

70:1

All packages include: XTR702 spray gun, 10.5 m (35 ft) hose, 500 bar (7250 psi) circulation manifold and standard mix manifold.

		CART	26 LITRE (7 GALLON) HOPPERS	SOLVENT	VISCON HF - HAZ LOC HEATERS (2)	VISCON HF - NON HAZ LOC HEATERS (2)	NON HAZ LOC JUNCTION BOX	VISCON HP - HAZ LOC HEATER (HOSe)	VISCON HP - NON HAZ LOC HEATER (HOSe)	HEATED HOSE CIRC KIT	PRESSURE TRAK	A/B LOWER SIZES (cc)
	572250											180/72
	572251	•										180/72
(2.5:1 MIX RATIO)	572252	•	•									180/72
X R	572253	•		•	•							180/72
Ξ	572254	•	•	•	•							180/72
	572255	•	•	•		•	•					180/72
(2)	572256	•	•	•	•			•		•	•	180/72
	572257	•	•	•		•	•		•	•	•	180/72
												_
	572300											220/72
	572301	•										220/72
(2)	572302	•	•									220/72
(3:1 MIX RATIO)	572303	•		•	•							220/72
Ĭ	572304	•	•	•	•							220/72
3:1	572305	•	•	•		•	•					220/72
٠	572306	•	•	•	•			•		•	•	220/72
	572307	•	•	•		•	•		•	•	•	220/72
												·
	572400											220/54
	572401	•										220/54
()	572402	•	•									220/54
(4:1 MIX RATIO)	572403	•		•	•							220/54
Ĭ	572404	•	•	•	•							220/54
<u>-</u>	572405	•	•	•		•	•					220/54
٣	572406	•	•	•	•			•		•	•	220/54
	572407	•	•	•		•	•		•	•	•	220/54

See manual #3A4381 for complete ordering information.

Ordering Information



All packages include: XTR502 spray gun, 10.5 m (35 ft) hose, 350 bar (5000 psi) circulation manifold and standard mix manifold.

			(N)									
		CART	26 LITRE (7 GALLON) HOPPERS	SOLVENT PUMP	VISCON HF - HAZ LOC HEATERS (2)	VISCON HF - NON HAZ LOC HEATERS (2)	NON HAZ LOC JUNCTION BOX	VISCON HP - HAZ LOC HEATER (Hose)	VISCON HP - NON HAZ LOC HEATER (HOSE)	HEATED HOSE CIRC KIT	PRESSURE TRAK	A/B LOWER SIZES (cc)
	573100											220/220
	573101	•										220/220
<u>(</u>	573102	•	•									220/220
.W	573103	•		•	•							220/220
(1:1 MIX RATIO)	573104	•	•	•	•							220/220
	573105	•	•	•		•	•					220/220
_	573106	•	•	•	•			•		•	•	220/220
	573107	•	•	•		•	•		•	•	•	220/220
									,			
	573150											220/145
=	573151	•										220/145
AT10	573152	•	•									220/145
(1.5:1 MIX RATIO)	573153	•		•	•							220/145
፟	573154	•	•	•	•							220/145
.5.	573155	•	•	•		•	•					220/145
<u> </u>	573156	•	•	•	•			•		•	•	220/145
	573157	•	•	•		•	•		•	•	•	220/145
									,			
	573200											290/145
=	573201	•										290/145
AT10	573202	•	•									290/145
X R	573203	•		•	•							290/145
(2:1 MIX RATIO)	573204	•	•	•	•							290/145
(2:1	573205	•	•	•		•	•					290/145
	573206	•	•	•	•			•		•	•	290/145
	573207	•	•	•		•	•		•	•	•	290/145

See manual #3A4381 for complete ordering information.

50:1

All packages include: XTR502 spray gun, 10.5 m (35 ft) hose, 350 bar (5000 psi) circulation manifold and standard mix manifold.

		CART	26 LITRE (7 GALLON) HOPPERS	SOLVENT	VISCON HF - HAZ LOC HEATERS (2)	VISCON HF - NON HAZ LOC HEATERS (2)	NON HAZ LOC JUNCTION BOX	VISCON HP - HAZ LOC HEATER (Hose)	VISCON HP - NON HAZ LOC HEATER (Hose)	HEATED HOSE CIRC KIT	PRESSURE TRAK	A/B LOWER SIZES (cc)
	573250											290/115
<u> </u>	573251	•										290/115
AII	573252	•	•									290/115
(2.5:1 MIX RATIO)	573253	•		•	•							290/115
₹	573254	•	•	•	•							290/115
5:1	573255	•	•	•		•	•					290/115
(2	573256	•	•	•	•			•		•	•	290/115
	573257	•	•	•		•	•		•	•	•	290/115
	573300											290/97
	573301	•										290/97
(3:1 MIX RATIO)	573302	•	•									290/97
RA RA	573303	•		•	•							290/97
Ê	573304	•	•	•	•							290/97
3:1	573305	•	•	•		•	•					290/97
<u></u>	573306	•	•	•	•			•		•	•	290/97
	573307	•	•	•		•	•		•	•	•	290/97
	573400											290/72
_	573401	•										290/72
1	573402	•	•									290/72
(4:1 MIX RATIO)	573403	•		•	•							290/72
Ê	573404	•	•	•	•							290/72
1	573405	•	•	•		•	•					290/72
"	573406	•	•	•	•			•		•	•	290/72
	573407	•	•	•		•	•		•	•	•	290/72

See manual #3A4381 for complete ordering information.



ABOUT GRACO

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS
P.O. Box 1441
Minneapolis, MN 55440-1441
Tel: 612-623-6000
Fax: 612-623-6777

AMERICAS

MINNESOTA
Worldwide Headquarters
Graco Inc.
88-11th Avenue N.E.
Minneapolis, MN 55413

EUROPE

BELGIUM

European Headquarters Graco Distribution BVBA Industrieterrein-Oude Bunders Slakweidestraat 31 3630 Maasmechelen Belgium Tel: 32 89 770 700

Tel: 32 89 770 700 Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd.
Suite 17, 2 Enterprise Drive
Bundoora, Victoria 3083
Australia
Tol: 61.2 0468 8500

Tel: 61 3 9468 8500 Fax: 61 3 9468 8599

CHINA

Graco Hong Kong Ltd.
Shanghai Representative Office
Building 7
1029 Zhongshan Road South
Huangpu District
Shanghai 200011
The People's Republic of China
Tel: 86 21 649 50088
Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd. India Liaison Office Room 432, Augusta Point Regus Business Centre 53 Golf Course Road Gurgaon, Haryana India 122001 Tel: 91 124 435 4208 Fax: 91 124 435 4001

JAPAN Graco K.K. 1-27-12 Hayabuchi Tsuzuki-ku Yokohama City, Japan 2240025 Tel: 81 45 593 7300 Fax: 81 45 593 7301

KOREA Graco Korea Inc. 38, Samsung 1-ro 1-gil Hwaseong-si, Gyeonggi-do, 18449 Republic of Korea Tel: 82 31 8015 0961

Fax: 82 31 613 9801

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco is certified ISO 9001.

Europe +32 89 770 700 FAX +32 89 770 777 WWW.GRACO.COM