



XHF™ Spray Gun

High-Flow, High-Pressure Gun



Designed for the most demanding materials

- Handles high viscosity protective coatings
- Designed for reduced plugging with epoxy intumescent coatings and fiber-filled materials
- Rugged and durable for less downtime

PROVEN QUALITY. LEADING TECHNOLOGY.



Rugged and Capable

Technical Specifications

Maximum working pressure	7250 psi (500 bar, 50 MPa)
Fluid orifice size	0.125 in (3.2 mm)
Inlet size	3/8 npt(m)
Weight (includes tip and tip guard)	1.45 lb (658 g)
Wetted parts	Tungsten carbide, 17-4PH passivated stainless steel, polypropylene, polyethylene
Manual	3A2799A

Ordering Information

XHF Gun

262854 XHF Gun, includes XHD 429 tip

Accessories

237260 XHF Gun repair kit

24P834 XHF Gun swivel, 1/2 in f x 3/8 npsm, PTFE packing, 6500 psi (448 bar, 44.8 MPa)

246294 10 in (254 mm) gun extension, 7250 psi (500 bar, 50 MPa)

246295 15 in (380 mm) gun extension, 7250 psi (500 bar, 50 MPa)

246296 18 in (457 mm) gun extension, 7250 psi (500 bar, 50 MPa)

246297 180° spray nozzle, 7/8 UNC-2B, 7250 psi (500 bar, 50 MPa)

XHD___ Heavy duty RAC® SwitchTip
(Last three digits correspond to tip size)

XHD001 XHD RAC housing, aluminum, hand tight - included with gun

XHD003 XHD RAC housing, SST, wrench tight - for extended thread life

Heavy fluid needle

- Maximize uptime
- No spring in fluid path



Front-entry fluid housing

- High pressure, up to 7250 psi (500 bar, 50 MPa)
- High flow and high production
- Ideal for fibrous or heavily filled materials

Four-finger trigger with safety lock

- Contoured for comfort

Ergonomic gun body

- Light weight forged aluminum
- Form fitted handle for less fatigue



Rugged, Reliable and Easy to Maintain

XHD™ RAC® SwitchTip™ and Housing

- Handles high solids coatings
- Hand-tight installation
- Tool-less tip removal

Contact us today!

For more information, call **1-877-844-7226**

or visit **www.graco.com**

©2013 Graco Inc. 348891 Rev. A 5/13. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.