

XHF™ Spray Gun

High-flow, high-pressure gun



Designed for the most demanding materials

- Handles highly viscosity protective coatings
- · Designed for reduced plugging with epoxy intumescent coatings and fibre-filled materials
- Rugged and durable for less downtime



Ordering information

XHF gun

262854 XHF gun, includes XHD 429 tip

Accessories

237260 XHF gun repair kit

24P834 XHF gun swivel, 1/2 in f x 3/8 npsm, PTFE packing, 448 bar (6500 psi, 44.8 MPa)

246294 10 in (254 mm) gun extension, 500 bar (7250 psi, 50 MPa)

246295 15 in (380 mm) gun extension, 500 bar (7250 psi, 50 MPa)

246296 18 in (457 mm) gun extension, 500 bar (7250 psi, 50 MPa)

246297 180° spray nozzle, 7/8 UNC-2B, 500 bar (7250 psi, 50 MPa)

XHD---- heavy duty RAC[®] SwitchTip (last three digits correspond to tip size)

XHD001 XHD RAC housing, aluminium, hand tight - included with gun

XHD003 XHD RAC housing, SST, wrench tight for extended thread life

Rugged and capable

Technical specifications

Maximum working pressure 500 bar (7250 psi, 50 MPa) Fluid orifice size 3.2 mm (0.125 in) Inlet size 3/8 npt(m) Weight (includes tip and tip guard) 658 g (1.45 lb) Wetted parts, tungsten carbide, 17-4PH passivated stainless steel, polypropylene, polyethylene Manual 3A2799A

Heavy fluid needle

Maximise uptimeNo spring in fluid path

Front-entry fluid housing

- High pressure, up to 500 bar (7250 psi, 50 MPa))
- High flow and high production
- Ideal for fibrous or heavily filled materials

Four-finger trigger with safety lock

· Contoured for comfort

Ergonomic gun body

- Light weight forged aluminium
- · Form fitted handle for less fatigue



Rugged, reliable and easy to maintain XHD[™] RAC[®] SwitchTip[™] and housing

11 11 12471-121

- · Handles high solids coatings
- Hand-tight installation
- Tool-less tip removal

GRACO DISTRIBUTION BV Industrieterrein Oude Bunders Slakweidestraat 31 • B-3630 Maasmechelen Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777 • www.graco.com

©2013 Graco Distribution BV 348891ENEU Rev. A 03/21 Electronic version only. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. For more information on Graco's intellectual property, see www.graco.com/patent or www.graco.com/ trademarks.