



ToughTek™ CM20

A Continuous Mixer that Plugs in Anywhere



High Production, Quality Results

- Plug and play – rated for a 230V circuit
- Simple operation and controls – water flow only needs to be set once
- Lightweight and portable – weighs 95kg and is easy to move around a worksite
- Easy disassembly for cleaning and transport

PROVEN QUALITY. LEADING TECHNOLOGY.

Let the Mixer do the Work

As the stucco, EIFS and mortar markets move towards pre-blended products, now is the time to consider a machine designed specifically for these materials. Say goodbye to the manual process of measuring and mixing by hand or batch mixer and switch to Graco's ToughTek CM20 continuous mixer.

To operate the machine, simply break pre-blended material into the hopper, turn the system on, and adjust the water flow rate to achieve the desired mix. Once the water flow is set, the CM20 will remain constant throughout the day to produce a consistent material mix.

For large jobs, the affordable CM20 continuous mixer achieves a higher output than traditional methods and comparable mixers while maintaining a high quality mix. In addition, the CM20 is the first continuous mixer on the market to be rated for a standard 230V circuit, enabling you to plug it in and start mixing anywhere on site.

Now is the time to switch to a continuous mixer that will keep your operations running continuously.

Large Capacity Hopper with Bag Breaker

- Ideal for large projects
- Output – up to 40 bags / hour

Quick-knockdown Mixing Section

- Tool-less clamp for simple assembly and disassembly
- Easy to clean and maintain

Compact and Portable

- Weighs only 95 kg
- Easy to move

Simple Controls

- Easy-to-use on/off toggle switch

Low Power Requirements

- Plugs into standard 230V, 1 ph wall outlet
- No electrician or rewiring needed

Water Flow Valve

- Set and adjust water flow
- Eliminates the need to measure water



Technical Specifications

- Output – Up to 40 bags of pre-blended stucco per hour
- Hopper holds up to 3 (36 kg) bags of pre-blended stucco
- Max aggregate size – 8 mm (5/16 in)

Ordering Information

25M563 – CM20 bare system

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco is certified ISO 9001.

GRACO DISTRIBUTION BVBA Industrieterrein Oude Bunders • Slakweidestraat 31 • B-3630 Maasmechelen
Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777 • <http://www.graco.com>

©2016 Graco Distribution BVBA 349866ENEU Rev. A 07/17 Electronic version only
All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

