



REACTOR[®] HEATED HOSE
Heated Hoses for Reactor Equipment

Ordering Information

Whip Hose

- 246050 1/4 in x 10 ft Whip Hose with Xtreme-Wrap, 2000 psi (138 Bar)
- 246055 1/4 in x 10 ft Whip Hose with Xtreme-Wrap, 3500 psi (241 Bar)

Xtreme Wrap Scuff Guard

- 24Y549 3/8 in x 50 ft Hose, 2000 psi (138 Bar), ground wire
- 24Y678 3/8 in x 50 ft Hose, 2000 psi (138 Bar), thermocouple fluid temperature sensor
- 24Y240 3/8 in x 50 ft Hose, 2000 psi (138 Bar), RTD fluid temperature sensor
- 24Y679 3/8 in x 50 ft Hose, 3500 psi (241 Bar), thermocouple fluid temperature sensor
- 24Y241 3/8 in x 50 ft Hose, 3500 psi (241 Bar), RTD fluid temperature sensor

Blue Mesh Scuff Guard

- 256549 3/8 in x 50 ft Hose, 2000 psi (138 Bar), ground wire
- 246678 3/8 in x 50 ft Hose, 2000 psi (138 Bar), thermocouple fluid temperature sensor
- 24K240 3/8 in x 50 ft Hose, 2000 psi (138 Bar), RTD fluid temperature sensor
- 246679 3/8 in x 50 ft Hose, 3500 psi (241 Bar), thermocouple fluid temperature sensor
- 24K241 3/8 in x 50 ft Hose, 3500 psi (241 Bar), RTD fluid temperature sensor

No Scuff Guard

- 246075 3/8 in x 50 ft Hose, 2000 psi (138 Bar), ground wire
- 246046 3/8 in x 50 ft Hose, 2000 psi (138 Bar), thermocouple fluid temperature sensor
- 24T839 3/8 in x 50 ft Hose, 2000 psi (138 Bar), RTD fluid temperature sensor
- 249588 3/8 in x 50 ft Hose, 3500 psi (241 Bar), ground wire
- 246053 3/8 in x 50 ft Hose, 3500 psi (241 Bar), thermocouple fluid temperature sensor
- 24U743 3/8 in x 50 ft Hose, 3500 psi (241 Bar), RTD fluid temperature sensor

Accessories

- 25M493 Xtreme-Wrap for 50 ft hose section
- 25M494 Xtreme-Wrap for 10 ft hose section
- 25M495 Joint Protector

Refer to Manual 309572 for a complete list of heat hose assemblies.

Improved Hose Design

Graco's heated hoses are designed specifically for use with Graco Reactors. Now, the multi-strand copper heating element that greatly increased the quality of the whip hoses is now available on all heated hoses!

- Provides 10-times* the flex life compared to previous flat copper heating element (*testing based on 1/4 in 2000 psi heated hose)
- Long-term, even heating without hot spots
- Backwards compatible with existing Reactor heated hoses

Keep your hose investment safe with the new Xtreme-Wrap™ Scuff Guard and Joint Protectors

Xtreme-Wrap Scuff Guard provides extra protection and prolonged life to your hose. You may choose a hose that is factory installed with Xtreme-Wrap or purchase the kit to retrofit any existing Graco hose.

- Form fitting to the hose, no more baggy excess material
- Made from urethane coated ballistic nylon for puncture and tear resistance, abrasion protection, and oil and water resistance
- Sheds surface moisture and won't absorb water to weigh down the hose bundle; will not freeze solid in cold temperatures
- Hook and Loop enclosure used on the entire length of the hose for easy access to the hoses, fittings, and fluid temperature sensors
- All whip hoses are factory installed with the improved Xtreme-Wrap

Joint Protectors

Joint Protectors provide additional protection at the most vulnerable section of the hose: the electrical connections, hose fittings, and fluid temperature sensors.

- Hook and loop closure for easy access
- All 50 ft hoses with Xtreme-Wrap will come with one Joint Protector



Graco Reactor hoses are ETL Certified and carry the ETL Listed Mark

In order to maintain your Reactor system ETL certification, ETL approved hoses must be used.



➔ **Contact us today!**

Call **866-361-5959** to talk with a Graco representative, or visit www.graco.com for more information.

