

Wastewater and Water Industry

Material and equipment for the maintenance and support of the water industry



PROVEN QUALITY. LEADING TECHNOLOGY.

► Protective Coatings Materials & Equipment

Whether it's a storage tank, manhole or wastewater facility, Graco's equipment helps your business get the job done quickly and efficiently. Select Raven 405 with a Graco XP plural-component sprayer for maximum protection of concrete and steel surfaces.

Epoxies



Raven 405

Raven 405 is a 100% solids, ultra-high build, solvent free epoxy coating formulated with exceptionally high physical properties and chemical resistance. The surface tolerance and high physical strengths of 405 allow it to be designed as a structural lining in manholes, pipelines, tanks and other deteriorated structures.

Recommended Spray Temperatures

115-145°F for Part A and 90-125°F for Part B. Temperature is dependent on ambient conditions and hose lengths. To equalize viscosities and reduce operating pressure, Part A should be 20°F warmer than Part B during processing.

Plural Component



XP50

Get your crew up and running quickly with this easy-to-operate pump. Graco XP50 plural-component sprayers are designed to pump, mix and atomize medium to high solid coatings with superior results. In addition, this sprayer provides excellent return on investment by reducing material waste and by using less clean-up solvent.



XP50-hf

The Graco XP-hf is designed with more flow capacity making it ideal for high output applications. With the powerful XL 10000 air motor, get 60% more flow than the XP sprayers. This also gives your crew the ability to use larger tips or run multiple guns, getting jobs done faster.