

## PROTECTIVE COATINGS SPRAY EQUIPMENT

**AUSTRALIA & NEW ZEALAND** 



### TRITON AIR SPRAY PACKAGE

# Diaphragm spray packages designed specifically for the finishing market.

Triton is an air-operated diaphragm spray package that applies a high quality, decorative finish to wood and metal parts. Triton is a more effective alternative to traditional pressure pots and standard diaphragm pumps.productivity and profitability.

- HIGH QUALITY FINISH
- EASY-TO-USE / CLEAN
- RUGGED CONSTRUCTION
- CART MOUNT / PORTABILITY
- DOUBLE DIAPHAGM DESIGN
- QUICK AND EASY FLUSHING REDUCES MATERIAL WASTE

TRITON AIR SPRAY PACKAGE	PART #
Triton Air Spray Package 1.4 mm nozzle	233482
Triton Air Spray Package 1.8 mm nozzle	26B364
9.5 L Pressure Pot	223833
Air fluid hose required for pressure pot	233499

THESE UNITS ARE INTRINSICALLY SAFE.



Unit comes with a 7.5 m fluid hose, AirPro conventional gun and nozzle.

#### 9.5 L PRESSURE POT

- PAINTED ALUMINIUM TANK
- DUAL REGULATOR OPTIONS FOR PULSATION-FREE DELIVERY
- BUILT-IN HANDLE FOR EASY
   MOVEMENT



## AIR SPRAY GUNS

# Air spray guns combine a low-pressure fluid stream with compressed air at the air cap to atomise material.

Graco supplies full spray package, pressure feed and gravity guns. Suited to the amount of painting you need to do. They required compressed air to run and provide top class finish. AirPro guns have a wide standard product offering with conventional gun models, in addition to compliant and HVLP. Ideal for metal, wood and high wear applications.

Here is a guide to tip sizes:

COATINGS GUIDE	NOZZLE SIZE MM
2 PACK POLY	1.4
QD ENAMEL	1.4 - 1.8
LACQUERS	1.4 - 1.8
STAINS	1.4
PRIMERS	1.8
VERY THICK PAINTS	1.8 - 2.8
BASE/CLEAR COATS	1.2 - 1.4
URETHANES	1.4 - 1.8
WATER BOURNE	1.4 - 1.8

TRANSFER EFFICIENCY		
CONVENTIONAL	GOOD	
COMLIANT	BETTER	
HVLP	BEST	

FINEX/AIRPRO GUNS	PART #
Finex Spray Gun, 1.4 mm nozzle pressure	289254
Finex Spray Gun, 1.8 mm nozzle pressure	289255
Finex Spray Gun, 1.4 mm nozzle, gravity feed	289244
Finex Spray Gun, 1.8 mm nozzle, gravity feed	289246
Pressure AirPro Spray Gun, 1.4 mm nozzle, conventional	288931
Pressure AirPro Spray Gun, 1.8 mm nozzle, conventional	288932
Pressure AirPro Spray Gun, 2.2 mm nozzle, conventional	288933
Pressure AirPro Spray Gun, 1.4 mm nozzle, HVLP	288938
Pressue AirPro Spray Gun, 1.8 mm nozzle, HVLP	288939
AirPro Spray Gun, 1.4 mm nozzle, gravity	289011
AirPro Spray Gun. 1.8 mm nozzle, gravity	289012



Finex Spray Gun Pressure Feed



Finex Spray Gun Gravity



AirPro Spray Gun Pressure Feed



AirPro Spray Gun Gravity

## MERKUR ES AIRLESS PACKAGE MERKUR AIR-ASSISTED PACKAGE

# Merkur ES is one of the most efficient sprayers designed to use less material and to reduce air usage and pulsation.

The Merkur Sprayers for light industrial coatings is ideal for touch-ups or other smaller projects. Its light weight and portability make it a great mobile auxiliary system to finish up a job in tight areas. Ideal for coatings that don't require the pressure and flow of a larger sprayer.

- HIGH QUALITY FINISH FAST, EFFICCIENT AND SIMPLE TO USE
- QUICK FLUSH SYSTEM REQUIRES LESS THAN 1 MINUTE TO FLUSH
- DELIVERS A SUPERIOR, CONSISTENT SPRAY FINISH, MINIMAL OVERSPRAY
- LIGTHWEIGHT, FLEXIBLE FLUID HOSE REDUCES MATERIAL AND SOLVENT USAGE
- AIR ASSISTED PROVIDES A SOFTER HIGHER QUALITY FINISH

The Merkur ES is available in Airless and Air-Assisted Airless ideal for metal primers, lacquers, 2 pack paint and quick dry enamels.

APPLICATIONS:
ENGINEERING SHOPS
TRUCK AND TRAILER
HORSE FLOATS
BOX TRAILERS
FURNITURE SHOPS
SKIP BINS
CABINETRY

MEDIUM-HIGH PRESSURE AIRLESS SYSTEM	PART #
Merkur 30:1 Airless Stand Mount	24F155
Merkur 30:1 Air Assisted Stand	24F157
Inline filter	24F272
Airless hose 3/16 x 7.6 m	214698

THESE UNITS ARE INTRINSICALLY SAFE. AIRLESS UNITS REQUIRE 10 CFM COMPRESSOR TO RUN AND Air-Assited 15 CFM.



Airless unit comes with a 7.5 m fluid hose, 163515 tip and Silver Plus airless gun.



Air-Assisted unit comes with a 2 x 7.6 m fluid hose, Air-Assited high performance gun with AAF412 tip.



# MEDIUM TO HIGH PRESSURE MERKUR UNITS

# Merkur pump packages are designed to improve productivity, reduce costs, lower emissions and provide consistent, high quality finishes for all of your demanding applications.

The Merkur spray packages are designed to outperform and outlast other pumps in their class. With a variety of models and configurations to choose from, you get the precise pressure and output you need for all of your finishing applications.

- OPTIMISED FOR PROTECTIVE COATING MATERIALS
- SPRAYS HIGH SOLID COATINGS (HOT POTTED EPOXIES AND URETHANES, SINGLE COMPONENT MATERIALS)
- ULTIMATE COMBINATION OF POWER AND PORTABILITY
- SUPPORT LONG HOSE LENGHTS FOR MANY COATINGS
- WEIGHTS ONLY 45 KG

MEDIUM-HIGH PRESSURE AIRLESS SYSTEM	PART #
Merkur X Airless Pump 48:1 - Max pressure 4800 psi	16U920
Merkur X Airless Pump 72:1 - Max pressure 7200 psi	16U918
Hopper 5 L polythylene	256410
Merkur Airless 30:1 - Max pressure 3000 psi	G30C55
Merkur AA 30:1 - Max pressure 3000 psi	G30C73



All systems come complete on trolley, flexible suction system, hoses, gun, tip and base.

#### THESE UNITS ARE INTRINSICALLY SAFE.



### XTR-5 and XTR-7 Guns - Lightweight and ergonomic

- NEEDLE ASSEMBLY AND XHD™ REVERSE-A-CLEAN (RAC)® SWITCHTIP™
- VARIETY OF HANDLE AND TRIGGER OPTIONS
- EASY OUT™ GUN FILTER
- TRIGGER GUARD
- EASYGLIDE™ SWIVEL

20	6
	-

XTR GUN	PART #
XTR5 Gun, 5000psi	XTR524
XTR7 Gun, 7250psi	XTR724
XTR5 Gun Hose Tip Kit*	273142
XTR7 Gun Hose Tip Kit*	273143
Gun filter 60/100 mesh	287034

\*Gun hose tip kit includes XTR gun, 15 m 3/8" hose, 1.8 m 1/4" whip hose, base 317, 319 tip.

SUITS MEDIUM-HIGH PRESSURE MERKUR AND KING UNITS.

### **HEAVY-DUTY AIRLESS KING**

# High-quality, high-volume, high-pressure! The Graco King pneumatic airless sprayers are the most powerful machines for protective coatings. Tried and proven Graco performance.

The system provides the applicator output values, pressure ratios and pumping capacities never seen before. The Graco King units are designed to withstand the harshest environmental conditions and easily handle the toughest protective coatings and corrosion control applications. With many different ratios available, there is a sprayer with the correct pressure and flow characteristics for your application.

- DESIGNED FOR HIGH SOLID COATINGS
- SIMPLE MAINTENANCE
- IMPROVED ICING PERFORMANCE
- LESS PULSATION
- MULTI GUN CAPABILITIES
- LONG LASTING HEAVY DUTY SPRAY PUMPS

TECH DATA		
RATIO	MAX PRESSURE	FLOW RATE
45:1	4500 PSI	17.4 L/min
60:1	6000 PSI	13.2 L/min
70:1	7000 PSI	10.8 L/min



HEAVY DUTY AIRLESS PUMP	PART #
King Airless Pump 45:1	K45FH2
King Airless Pump 60:1	K60FH2
King Airless Pump 70:1	K70FH2
38 L SS hopper	24X570
TSL Throat seal liquid 8oz bottle	206994

THESE UNITS ARE INTRINSICALLY SAFE. LOOK AT PAINT DATASHEET FOR RECOMMENDATION.

Unit comes complete on heavy duty trolley, flexible suction tube, 15 m x 3/8" airless hose, 1.8 m x 1/4" whip hose, XTR7 airless gun base and XHD519 tip.

\*\*All units are pneumatic and need compressed air to run.

### **High Pressure King Electric Pumps**

The Graco King E-series Electric Airless Sprayer is for protective coatings and select models have been approved for hazardous locations.



- E60/E70 DESIGNED FOR NON HAZARDOUS AREAS, THICK COATINGS, MEMBRANES AND INTUMESCENT
- E-XTREME EXPLOTION PROOF UNIT FOR CLASS 1 ZONE AND HAZARDOUS AREA

HIGH PRESSURE ELECTRIC PUMPS	PART #
E60 High Pressure Electric Pump	273752
E70 High Pressure Electric Pump	273746
E-Xtreme High Pressure Electric Pump	273246
8 m cable E-Xtreme	242267



E60 comes complete on trolley, includes: 15 m x 3/8" airless hose, 1.8 m whip hose, and XTR7 spray gun and tip.

E70 comes complete on trolley, includes: 15 m x 3/8" airless hose, 1.8 m whip hose and XTR7 spray gun and tip.

E-Xtreme includes: XTR7 spray gun, 519 tip, 3/8" x 15.2 m Xtreme-Duty-hose and 1.8 m whip hose.

# SURFACE PREPARATION VAPOUR BLASTING

## THE CLEANING ALTERNATIVE POWERFUL-PORTABLE-PROFESSIONAL

Prepping a surface can be challenging and time-consuming, especially if you are removing layers of paint or other coating products that have been there for decades. Grinding, scraping, applying heat and using chemicals are hard work because the same products that cause paint to adhere make it hard to remove. At the end of the day, it's about finding the best machine to get the job done guickly and with as little dust as possible.

- PORTABLE UNITS WITH LIFT HANDLES
- UP TO 92% LESS DUST THAN TRADITIONAL DRY BLASTING
- LOW WATER USAGE, LESS MESS
- FAST REMOVAL RATES
- EQp BLASTS FOR UP TO 90 MINUTES BETWEEN REFILLS
- EOM BLASTS FOR UP TO 2.5 HOURS BETWEEN REFILLS
- UP TO 75% LESS MEDIA USED
- LESS PPE REQUIRED







EQp packages include 15 m blast hose with pneumatic blast controls, #5 or #6 standard nozzle.

EQm packages include 30 m blast hose pneumatic blast controls, #7 standard nozzle and tool kit.



SURFACE PREPARATION VAPOUR BLASTING	PART #
Ecoquip EQp ATEX - Pneumatic 3/4" hose	278861
Ecoquip EQp ATEX - Pneumatic 1" hose	278862
Ecoquip EQm ATEX - Pneumatic 1" hose	262954

Larger models AVAILABLE upon request. Compressed air requirements EQp - 50-150 cfm EQm - 120-250 cfm

### TIPS

#### **RAC SWITCHTIPS**

The quality of your work is only as good as the quality of your finish. Graco's superior RAC SwitchTips are built to the highest standards and designed to consistently produce the best finish in the industry, every time.

- MAXIMISE YOUR RESULTS AND IMPROVE THE QUALITY OF YOU WORK
- 100% TESTED FOR FLOW RATE
- AVAILABLE IN A WIDE RANGE OF SIZES FOR DIFFERENT MATERIALS
- SPECIFIC COLOUR CODING FOR EACH APPLICATION

#### XHD RAC SWITCHTIP™

COMPLETE YOUR XHD TIP PART NUMBER USING THE NUMBERS IN THE CHARTS BELOW.

FOR EXAMPLE: FOR A TIP WITH .025 ORIFICE AND 254 MM (10 IN) PATTERN, ORDER XHD525.

FAN WIDTH - in (mm)	.007 .009 .011 .013 .015 .017 .019 .021 .023 .025 .027 .029 .031 .033 .035 .039 .043 .045 .051 .055 .063 .065	
2-4 (51-102)	— 109 111 — 115 — 119 121 — — — — — — — — — — — —	
4-6 (102-152)	207 209 211 213 215 217 219 221 223 225 — — — 235 — — — — —	
6-8 (152-203)	307 309 311 313 315 317 319 321 323 325 327 — 331 — — — — — — — —	
8-10 (203-254)	— 409 411 413 415 417 419 421 423 425 427 429 — 433 435 439 443 — 451 455 — —	The same of the sa
10-12 (254-305)	— 509 511 513 515 517 519 521 523 525 527 529 531 533 535 — 543 — 551 555 563 —	
12-14 (305-356)	— 609 611 613 615 617 619 621 623 625 627 629 631 633 635 — — 645 — 655 — 665	
14-16 (356-406)	721 723 725 729 735	
16-18 (406-XXX)	— — — 815 817 819 821 — — 827 — 831 833 835 — — — — — —	9
18-20 (457-508)	917 935	
Flow rate (GPM)	.05 .09 .12 .18 .24 .31 .38 .47 .57 .67 .77 .90 1.031.17 1.311.631.982.17 2.793.254.264.53	
Flow rate (LPM)	.20 .33 .49 .69 .91 1.17 1.47 1.79 2.15 2.54 2.96 3.42 3.90 4.42 4.98 6.18 7.51 8.23 10.57 12.29 16.13 17.17	
	2-4 (51-102) 4-6 (102-152) 6-8 (152-203) 8-10 (203-254) 10-12 (254-305) 12-14 (305-356) 14-16 (356-406) 16-18 (406-XXX) 18-20 (457-508) Flow rate (GPM)	2-4 (51-102) — 109 111 — 115 — 119 121 — — — — — — — — — — — — — — — — — —

#### LOW PRESSURE RAC X SWITCHTIPS (LPXXX)

FAN WIDTH - in (mm)	.013	.015	.017	.019	.021	.023	.025	.027	.029	.031
6-8 (152-203)	3	13 3 <sup>-</sup>	15 —	-		-			_	- —
8-10 (203- 254)	_	– 4 <sup>-</sup>	15 41	7 4	19 42	21 42	23 42	25 —	- –	- —
10-12 (254-305)	_	515	517	519	521	523	525	527	_	_
12-14 (305-356)	_	_	617	619	621	623	625	627	629	631
14-16 (356-406)	_	_	_	_	_	723	725	_	729	731

#### FINE FINISH LOW PRESSURE RAC X SWITCHTIPS (FFLPXXX)

FAN \	WIDTH - in (mm)	.008	.010	.012	.014	.016
2-4	(102-152)	108	110	112	_	_
4-6	(102-152)	208	210	212	214	_
6-8	(152-203)	308	310	312	314	_
8-10	(203-254)	_	410	412	414	_
10-12	2 (254-305)	_	510	512	514	516
12-14	1 (305-355)	_	_	_	_	616

Lowering spray pressure can reduce flow in some materials. Increase tip orifice size to maintain speed and material flow if needed.

#### **ABOUT GRACO**

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coatings, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

AUSTRALIA
Graco Australia Pty Ltd.
Suite 17, 2 Enterprise Drive
Bundoora, Victoria 3083
Australia
Tel: 61 3 9468 8500
Fax: 61 3 9468 8599
NZ Toll Free Number: 0800 472 261

3C0005ENAP-B ©2021 Graco Australia 03/21. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication.

Graco reserves the right to make changes at any time without notice.

For more information on Graco's intellectual property, see www.graco.com/patent or www.graco.com/trademarks

