

ToughTek®

Complete Line of Cementitious Fireproofing Solutions





SOLUTIONS FOR ALL CEMENTITIOUS **MATERIALS!**

MATERIAL AND APPLICATION GUIDE

Every job has different requirements and demands, and we have you covered! Whether you are applying low, medium or high density cementitious fireproofing, we have a solution for you!

	F340e (up to 20 bags per hour)	F800e (up to 40 bags per hour)	P30X-HT (up to 20 bags per hour)	P40 (up to 40 bags per hour)
Low Density (15-21 lb per cubic foot)	х	х	х	х
Medium Density (23-39 lb per cubic foot)			х	х
High Density (Over 39 lb per cubic foot)			Х	Х

BIG PERFORMANCE IN A SMALL 120 VOLT PACKAGE!

When you're doing small jobs or patch work, look no further than the F340e. With it's compact size and unmatched performance, it outperforms other patch pumps so you

ToughTek® F340e PISTON PUMP PERFORMANCE

Adjustable Material

Dial in the exact flow needed

High or low flow— you decide!

Durable Frame

polyethylene hopper

with lid holds a full

for years of service

Hopper Removal

Disconnect in seconds

for easy cleaning

bag of mixed material

All steel frame construction

and Hopper

20 Gallon

Tool-less

Flow Control

for your job



ToughTek F800e PISTON PUMP PERFORMANCE

When you need a high-production sprayer on medium to large jobs, look no further than the F800e. Designed to replace large and heavy tow-behind sprayers, this portable sprayer can spray up to 40 bags per hour. Equipped with dual Quick-Access Piston Pumps, this system offers dramatically longer life and lower cost of ownership than rotor stator pumping systems.

45 Gallon Molded Hopper

- · Easily mix and pour with standard batch mixers
- · Optimized for smooth flow with bottom-feed inlets
- · Holds 2 full bags of mixed material

Toolbox

• Store your day-to-day essential sponge balls another parts

Dual Piston Pumps

- Quick-Access design for easy maintenance
- Heavy-duty steel construction with long-life seals for unmatched life
- Optimized specifically for low-density cementitious fireproofing

Ouick Disconnect

· Remove in seconds

for easy cleaning

and inspection

Inlet Clamps

MaxPower Brushless DC Motor

• Powerful 4.5 hp motor runs on standard 240V 30A single phase

power for added convenience

· Maintenance free design Totally-enclosed design keeps

dust and debris out

See the F800e in action!

Material Output:	Up to 40 Bags Per Hour		
Max psi (bar):	600 (42)		
Power Input:	240V, 30A, 1PH		

Controls

- Simple, easy to use and operate
- Fully adjustable flow control

2 Inch Camlock Outlet

- Oversized outlet for maximum flow
- No-tools hose connection

Tool-less Outlet Manifold

- · Allows for easy disassembly for easy cleaning and maintenance
- · Oversized passages for

maximum material flow

ROTOR STATOR "DO IT ALL" SOLUTIONS

When you are looking for a simple, yet capable pump, look no further than a Graco rotor stator pump. Consisting of only 2 parts, these innovative pumps are easy to maintain and can pump the widest range of materials with a steady, consistent flow

can finish jobs up to 2X faster - while using longer hose lengths and smaller diameter hose. Graco's rugged Quick-Access Piston Pump offers long life and lower cost of

- Compact and Portable
- Flatproof tires roll easily across the jobsite

- High-torque = more work done
- Totally-enclosed design keeps dust and debris out

Quick-Access Piston Pump

- easy maintenance
- · Heavy-duty steel construction with long-life seals for unmatched life
- Optimized specifically for Low

· Weighs only 210 lb

Easy to transport

MaxPower Brushless DC Motor

- Maintenance free design

- · Quick-Access design for
- **Density Fireproofing Materials**

ToughTek P30X-HT

When you need to pump the full range of materials, nothing beats a powerful rotor stator pump like the P30X-HT! Equipped with an oversized, extra-wide hopper, this is the perfect unit for use with your batch mixer on your fireproofing jobs!



Material Output:	Up to 20 Bags Per Hour		
Max psi (bar):	300 (21)		
Power Input:	240V, 30A, 1PH		

ToughTek P40

Know as the workhorse because of its 600 psi output pressure, the ToughTek P40 is built for high volume applications of any cementitious material. The high flow rate and high pressure allows contractors to pump with extended hose lengths to reach anywhere.



Material Output:	Up to 40 Bags Per Hour	
Max psi (bar):	600 (42)	
Power Input:	240V, 25A, 3PH	



See the F340e in action!

Material Output:	Up to 20 Bags Per Hour
Max psi (bar):	600 (42)
Power Input:	120V, 15A

ownership than rotor stator systems.

CONVENIENT

120V POWER!

- Plugs into standard

120V wall outlet

- No electrician or

rewiring needed

PRODUCT SPECIFICATIONS









	F340e	F800e	P30X-HT	P40
Туре	Piston Pump	Dual Piston Pump	RS Pump (R8-1.5)	RS Pump (U356)
Material Output	20 bags per hr	40 bags per hr	20 bags per hr	40 bags per hr
Maximum Flow Rate	12 gpm (45 lpm)	26 gpm (98 lpm)	9.8 gpm (37.1 lpm)	18.7 gpm (70.8 lpm)
Maximum Pressure	600 psi (42 bar)	600 psi (42 bar)	300 psi (21 bar)	600 psi (42 bar)
Maximum Particle Size	3/16 in (5 mm)	3/16 in (5 mm)	1/4 in (6 mm)	1/4 in (6 mm)
Maximum Hose Length	150 ft (46 m)	300 ft (91 m)	250 ft (76.2 m)	400 ft (184 m)
Power Input	120V, 15A,	240V, 30A, 1PH	240V, 30A, 1PH	240V, 25A, 3PH
Pump Outlet Size	1.5 in (38 mm) Camlock	2.0 in (51 mm) Camlock	1.5 in (38 mm) Camlock	2 inch is 51mm Camlock
Chemical Compatibility	Water Based Materials	Water Based Materials	Water Based Materials	Water Based Materials
Hopper Capacity	20 gal (76 l)	40 gal (152 l)	63 gal 239 l)	19 gal (72 l)
System Weight	210 lb (95 kg)	385 lb (175 kg)	440 lb (200 kg)	530 lb (240 kg)
System Options			Remote Switch	Remote Switch
Manual	3A6393	3A5653	3A4361	3A4361
Part Numbers	25B503 (Pkg, includes: Applicator, Remote, (1) 1-3/8 in x 25 ft Hose, (1) 1 in x 25 ft Hose) 25B502 (bare, w/Remote)	25M810 (Pkg, includes: Applicator, Remote, (2) 2 in x 50 ft Hose, (1) 1-3/8 in x 50 ft Hose, (1) 1-3/8 in x 25 ft Hose, (1) 1 in x 25 ft Hose) 25M800 (bare, w/Remote)	25M141 (Pkg, includes: Applicator, (1) 1-3/8 in x 50 ft Hose, (1) 1-3/8 in x 25 ft Hose, (1) 1 in x 25 ft Hose) 25M041 (bare)	25M050 (Bare)

ACCESSORIES

27A456 Fireproofing Spray Kit Includes: Fireproofing Pole Applicator, 1-3/8 in x 50 ft (35 mm x 15 m) Hose, 1-3/8 in x 25 ft (35 mm x 7.5 m) Hose, 1 in x 25 ft (25mm x 7.5m) Hose and required adapters (uses Camlock Couplings)	27A456 Fireproofing Spray Kit Includes: Fireproofing Pole, Applicator, 1-3/8 in x 50 ft (35 mm x 15 m) Hose, 1-3/8 in x 25 ft (35 mm x 7.5 m) Hose 1 in x 25 ft (25 mm x 7.5 m) Hose and required adapters (uses Camlock Couplings) Requires 25D854 Camlock Adapter	27A456 Fireproofing Spray Kit Includes: Fireproofing Pole, Applicator, 1-3/8 in x 50 ft (35 mm x 15 m) Hose, 1-3/8 in x 25 ft (35 mm x 7.5 m) Hose 1 in x 25 ft (25 mm x 7.5 m) Hose and required adapters (uses Camlock Couplings)	27A456 Fireproofing Spray Kit Includes: Fireproofing Pole, Applicator, 1-3/8 in x 50 ft (35 mm x 15 m) Hose, 1-3/8 in x 25 ft (35 mm x 7.5 m) Hose 1 in x 25 ft (25 mm x 7.5 m) Hose and required adapters (uses Camlock Couplings) Requires 25D854 Camlock Adapter
25D855 Camlock Adapter: 1.5 in x 1 ft (38 mm x 25 mm)	27A005 2 in x 50 ft (50 mm x 15 m) Material Hose	MTA787 Remote Switch, 40 ft	MTA787 Remote Switch, 40 ft
27A002 1 in x 25 ft (25 mm x 7.5 m) Material Hose	25D854 Camlock Adapter 2.0 in (f) x 1.5 in (m) (50 mm x 35 mm)	MTA788 Remote Switch Extension, 50 ft	MTA788 Remote Switch Extension, 50 ft
27A003 1-3/8 in x 50 ft (35 mm x 15 m) Material Hose	27A003 1-3/8 in x 50 ft (35 mm x 15 m) Material Hose	27A003 1-3/8 in x 50 ft (35 mm x 15 m) Material Hose	25D854 Camlock Adapter: 2.0 in (f) x 1.5 in (m) (50 mm x 35 mm)



Every Graco purchase comes with A+ Customer Service.

Questions? Call (844) 241-9499 Contact us today! Visit www.graco.com/toughtek to learn more or have a Graco representative contact you.

For more information visit graco.com