



# TOUGHTEK® P30HT

Rotor Stator Pump

## SIMPLE YET POWERFUL!

When the job requires thicker, hard-to-pump materials, nothing beats a powerful rotor stator pump like the P30HT! Perfect for pumping self-leveling compounds, stucco, epoxy-based stucco, repair mortar or other thick high-viscosity materials, this is a great solution for the big jobs.



### **Perfect for any jobsite!**

The durability and rugged performance needed to get the job done quickly



### **One pump — many applications**

A perfect blend of high-performance, material capability and versatility to do it all!



## BENEFITS YOU'LL APPRECIATE!

**High performance** — Pump up to 175 bags an hour of self leveling materials, or up to 30 bags an hour of repair mortars and stucco

**Large aggregate capable** — Pumps the full range of material up to 1/4 in (6 mm) aggregate size

**Long distance pumping** — Allows positioning of equipment and material in a single location to save time

**Small footprint** — Easy to maneuver and position where you need it

**Easy maintenance** — two-piece adjustable pump with rotor and stator = minimal wear parts to maintain



# TOUGHTEK P30HT

Rotor Stator Pump

## THE PERFECT FIT FOR YOUR BUSINESS!

If you're looking for versatility and performance with high-viscosity materials, the ToughTek P30HT is the perfect fit for your business. Featuring Graco's innovative 2-part adjustable rotor stator pump, this innovative pump is easy to maintain and can pump the widest range of materials with a steady, consistent flow.

### Variable Frequency Drive

- Protects your investment — provides auto shutdown in case of power spikes

### Feed Gate

- Impedes entry of large foreign objects to minimize downtime

### Heavy Duty Frame

- All steel construction for years of service
- Oversized tires easy maneuver through any jobsite

### Reversible Drive

- Easily change pump direction to relieve fluid pressure and packouts

### Adjustable Stator

- Adjust output pressure, as desired
- Extends the life of the stator sleeve

### Simple Control

- Easy dial control for desired output
- Heavy duty steel frame can be positioned where you need it

### Modular Frame Design

- Easy removal of motor/gearbox and pump for improved portability



TOUGHTEK P30HT	PART#
Bare	25M032
Package Includes: Stucco Applicator with Nozzles, 1-3/8 in x 50 ft (35 mm x 15 m) Material Hose.	25M132

SPECIFICATIONS	PART#
Material Output	9.8 gpm (37.1 lpm) – Up to 30 bags per hour (stucco) Up to 175 bags per hour (self-leveling)
Max psi (bar)	300 (21)
Max Particle Size	1/4 in (6 mm)
Max Hose Length	150 ft (45 m)
Hopper Capacity	19 gal (72 l)
Pump Size	R8-1.5
Pump Outlet	1.5 in (38 mm) Camlock
Weight	320 lb (145 kg)
Power Input	240V, 25A, 1PH

ACCESSORIES	PART#
Remote Switch, 40 ft	MTA787
Remote Switch Extension, 50 ft	MTA788
1-3/8 in x 50 ft (35 mm x 15 m) Material Hose	27A004
1-3/8 in x 25 ft (35 mm x 7.5 m) Material Hose	27A003
Stucco Applicator with 1.5 in Camlock Fitting	25D852
Rotor/Stator Kit R8-1.5	MTA750
Static Mixer Kit	25C823



Every Graco purchase comes with A+ Customer Service.

Questions?  
Call (844) 241-9499



**Contact us today!** Visit [www.graco.com/toughtek](http://www.graco.com/toughtek) to learn more or have a Graco representative contact you.