



The Industry Standard in Petrol-Powered Airless Sprayers



GMAX[™] II (HD 3-IN-1) Standard

Petrol-Powered Airless Sprayers for Professionals

For Everyday Reliability!

If you're looking for technology that gets the job done, this is for YOU. Technology that has proven to do the trick, time and time again. The GMAX II family consists of Graco's most popular petrol-powered Airless sprayers for professionals. With over 25 years' experience in providing proven quality and unmatched onthe-job productivity, it has become an industry standard. A standard you can trust to get the job done.

THE STANDARD SERIES are suited for professionals that don't need extras but are looking for everyday reliability to get the job done quickly and easy.

CHOOSE THE RIGHT UNIT

The GMAX II range is ideally suited for high-production professional contractors who demand uninterrupted performance without the need for electric power.

The GMAX II 3900 (120 cc) is the perfect sprayer for professional paint jobs on new residential construction job sites.

The GMAX II 5900 is a step up from that. With its 200 cc Honda engine, it delivers the output you require for larger commercial paint projects. Along with its high performance 200 cc Honda® engine, the GMAX II 7900 HD is equipped with a heavy duty pump, enabling it to easily spray all thicker coatings as well as the full range of primers and paints.

... and go for the Standard Series for everyday reliability! Take a look at the features that have turned our GMAX II range into the industry standard. Discover this standard, like so many other professionals have already.

Endurance[™] Chromex[™] Piston Pump

Repack the pump in minutes with the new QuikPak Cartridge System

- QuikChange[™] pump design allows you to swap the pump easily on the job
- Faster cleaning with the QuikAccess™ intake foot valve
- All GMAX II 7900 sprayers feature Graco's extreme-duty MaxLife[™] Pump with both MaxLife sleeve and rod





Honda® Engines

The industry standard engine for the industry standard sprayer!

All GMAX II units are equipped with Honda® engines (contractor preferred) that deliver unmatched performance to the pump.



Advantage Drive™

The drive is the critical link between the engine and the pump. Graco doesn't leave the production of our Advantage Drive System to others; we design and manufacture it at our world-class manufacturing facility in the United States.

- Hardened steel gears run extremely quietly
- The most durable, longest lasting drive in the industry



SmartControl™ 3.0 with Pressure Gauge

Graco's advanced SmartControl 3.0 offers precision pressure control that delivers a consistent spray fan without pressure fluctuations.

- Spray thicker coatings and run longer hoses

Materials & Applications

The GMAX II STANDARD series are ideal for spraying a full range of coatings during residential, commercial and industrial jobs.

Spray acrylics, primers, emulsions, waterborne and solvent-based paints with the 3900 and 5900, or upgrade to the 7900 HD to handle most common anti-corrosive and fire-retardant paints and Airless plasters as well!







Contractor PC[™] Gun

FINISH JOBS FASTER WITH LESS FATIGUE **Premium Comfort for All-Day Spraying**

it easier to clean and

maintain your pump.

Semi-Pneumatic

Wheels - Roll easily over rough terrain

- ➤ Lightest gun in its class
- ➤ Up to 50% lighter trigge pull force
- ➤ E-Z Fit adjustable trigger length PATENT PENDING

REDUCE DOWNTIME WITH PROCONNECT **Complete Gun Rebuild** in Seconds PATENT PENDING

➤ Needle and all wear parts in one simple cartridge











EXTEND YOUR SPRAYING AUTONOMY

When used with a hopper or container suction kit, you can work for longer periods of time before refilling. Use for overnight storage or to transport your material. You will save energy, time and money.



Always begin working at low material pressure.

Gradually raise the pressure, but only to the minimum pressure required for successful application. Using too much pressure can cause pack-out due to aggregated materials or dirt.

For improved pump performance when spraying paint with the GMAX II 7900 HD unit, replace the ceramic ball in the lower pump with the SST ball (delivered free of charge with the unit).





PATENT PENDING

OLD way

NEW way

Modular pre-oiled cartridge packings install correctly every time

QuikPak™ Cartridge System

Repack the entire pump in minutes



Insert pre-oiled packing cartridge assembly



Remove disposable clip



Assemble pump

GMAX[™] II (HD 3-IN-1) Standard







GMAX II (HD 3-IN-1) Standard

| | 3900 | 5900 (5900 HD) | 7900 (7900 HD) |
|---------------------------------------|----------------|---------------------------------|---------------------------------|
| Part Numbers: | 17G999 | 17H810 (17H819) | 17H818 (17H820) |
| Max. Tip Size: 1 gun | 0.036" | 0.043" | 0.047" |
| Max. Flow - I/min (gpm) | 4.7 (1.25) | 6.0 (1.6) | 8.3 (2.2) |
| Max. Pressure - bar (PSI) | 227 (3300) | 227 (3300) | 227 (3300) |
| Engine displacement - cm ³ | 120 | 200 | 200 |
| Pump | Paint | Paint (HD Texture) | Paint (HD Texture) |
| Piston rod | Chromex™ | Chromex (Hard Chrome) | MaxLife [™] |
| Sleeve | Hard Chrome | Hard Chrome | MaxLife |
| MaxFlo [™] 2 | _ | - (✓) | - (✓) |
| Gun | Contractor PC™ | Contractor PC (HD Blue Texture) | Contractor PC (HD Blue Texture) |
| Tips | 517 | 517 (427,531) | 517 (427,531) |
| Hose | 1/4" x 15 m | 1/4" x 15m (3/8" x 15 m) | 1/4" x 15 m (3/8" x 15 m) |
| Whip hose | _ | (1/4" X 0.9 m) | (1/4" X 0.9 m) |
| Weight - kg (lbs) | 50 (109) | 64 (139) | 67 (146) |

UNPACK, PLUG & SPRAY! Ready to go: the GMAX II Standard Series shipped complete and ready to spray. SmartControl™ 3.0, TiltBack™ cart design, whip hose, BlueMax™ II hose, 246215 RAC X HandTite™ guard, gun, 206994 TSL™ 0.25 litre.

Accessories Get the most out of your equipment by using our professional accessories:

| Guns | | RAC X™ Tip Extensions | | Additional Accessories | |
|---------------------------------|---|---------------------------|-----------------------|---|---------------------------------------|
| 17Y043 | Contractor PC [™] Airless gun, | 287019 | 25 cm | 287987 | 90-litre hopper kit |
| | RAC X 517 | 287020 | 40 cm | 289587 | Bag roller |
| 289605 | TexSpray [™] blue gun with RAC X guard | 287021 | 50 cm | 24M445 | Heavy duty container suction kit |
| | and RAC X 531 tip | 287022 | 75 cm | | 40 cm, 2" hose with 1" to DIN C clamp |
| 245820 | Inline™ 4-finger plaster gun, | CleanShot™ RAC X Pole Gun | | | connectors. |
| | 280 bar | 287026 | 90 cm | | |
| | | 287027 | 180 cm | | |
| Gun-Tip-Hos | e Kits | | | Easy Out™ Gun Filters | |
| 17Y051 | Contractor PC gun, 1/4" X 15 m hose, | Hoses (230 | bar) | 287032 Easy Out gun filter, 60 mesh x 1 | |
| | 3/16" x 0.9 m whip, | 240794 | 1/4" x 15 m | 287033 | Easy Out gun filter, 100 mesh x 1 |
| | RAC X 517 | 240797 | 3/8" x 15 m | 287034 | Kit: 60 mesh x 1 + 100 mesh x 1 |
| 289611 | TexSpray blue gun, 3/8" X 15 m hose, | 223771 | 1/4" x 30 m | | |
| | 1/4" x 0.9 m whip, RAC X 531/427 tip, | 241275 3/8" x 30 m | | Easy Out™ Pump Filters | |
| | 276 bar | 241272 | 1/4" x 20 m | 244071 | 30 mesh, grey |
| 289585 | Inline 4-finger plaster gun, 1/2" | | | 244068 | 100 mesh, blue |
| | x 15 m hose, 3/8" x 3.6 m whip, | Whips (230 bar) | | 244067 | 60 mesh, black |
| | RAC X 643 + WA 1239 tip, 280 bar | 238358 | 3/16" x 0.9 m | 244069 | 200 mesh, red |
| | | 238959 | 3/16" x 1.4 m | | |
| Standard Endurance™ Pump Lowers | | 238359 | 3/16" x 1.8 m | Liquids | |
| 16Y598 | GMax II 3900 | | | 206994 | TSL™ 0.25 I |
| 16Y706 | GMax II 5900 | Hose Connectors | | 253574 | Pump Armor™ 1 I |
| 16X429 | GMax II 5900 HD | 156971 | 1/4" x 1/4" (M) x (M) | 245133 | Pump Armor 3.8 I |
| 16X423 | GMax II 7900 | 157350 | 1/4" x 3/8" (M) x (M) | | |
| 25E689 | GMax II 7900 HD | | | | |

For more information regarding other GMAX II sprayers: GMAX II (HD 3-IN-1) ProContactor Series: leaflet 300719 - GMAX II (HD 3-IN-1) IronMan Series: leaflet 300769



We're here to answer questions and help address your needs:

www.graco.com/contact

Graco is certified ISO 9001.

