G3[™] Pump with Auto-Fill Shutoff



Clean, Trouble-free Refilling Without Using Electronics





Eliminates Over- or Under-Filling

- Completely fill the reservoir every time while avoiding costly spills
- Does not require power to operate
- Complies with stringent mining regulations where a system must be powered down during fluid refilling
- Compatible with fast-fill-equipped lubrication trucks

Reservoir Full Visual Indication

- Valve Plate activates a poppet valve, which cuts off grease flow into the reservoir
- Poppet indicator can incorporate a signal switch for ground level monitoring

G3[™] Lubrication Pumps Featuring Auto-Fill Shutoff

Versatile line of G3 Pumps (Standard, Pro, and Max) offered with a factory-installed Auto-Fill Shutoff (AFSO). The AFSO feature automatically shuts off lubricant flow from a fill pump to the G3 reservoir once the G3 reservoir is full, eliminating the need to monitor the reservoir level during refilling.

The G3 AFSO is based on the same design concept as the Auto-Fill Shutoff offered in conjunction with the robust Electric Dyna-Star product line. Eliminate the need to climb up on equipment to refill an empty reservoir by adding Remote

Fill Manifold 77X542 to your system at ground level.

		Voltage	G3 Model	Reservoir Size		Number of Cycle/	Vent	Wiper Arm	Low Level	Power	
				4 liter	8 liter	Pressure Input	Valve Output*	Wiper Airii	LOW FEAGI	Connection	
Application	Grease	24 VDC	Standard	96G210	96G213			•	•	DIN	
				-	96G217			•	•	5 Wire CPC***	
			Pro	96G211	96G214			•	•	5 Wire CPC**	
			Max	96G212	96G215	1	•	•	•	5 Wire CPC**	
		90-240 VAC	Standard	-	96G207			•	•	DIN	
			Pro	-	96G208			•	•	DIN	
			Max	-	96G209	1	•	•	•	DIN	

^{*}If not connected, use part number 16T854 to cover the Vent Valve Output and maintain IP69K rating.

Remote Fill Manifold

Part Number	Description		
77X542	Remote-fill port manifold with vent		
121474	Female coupler		



Electronic Use Only

©2021 Graco Inc. 352584 Rev. C 9/21 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

AFSO Field Conversion Kits

	Part Number	Description		
	571286	G3 AFSO 4L Field Conversion Kit		
A	571287	G3 AFSO 8L Field Conversion Kit		
	571288	G3 AFSO 12L Field Conversion Kit		
111	571289	G3 AFSO 16L Field Conversion Kit		
W 100				

571287

Contact us today!

Call **800-533-9655** to speak with a Graco representative, or visit **www.graco.com** for more information.



[&]quot;G3 Max pumps with the 5 Wire CPC power connection are compatible with a Remote Manual Run/Monitoring Light Device to provide external fault indication. Choose part number 571030 for 12 VDC pumps or 571031 for 24 VDC pumps.

^{***}Low level in CPC.