G3[™] HAMMER PUMPS







PROVEN QUALITY. LEADING TECHNOLOGY.

Extend the life of your hydraulic hammer/breaker tools and provide a breakthrough for your budget. The new G3 Hammer Pump offers convenient top fill access, enabling chisel paste to be quickly added to the reservoir to avoid halting operations.

Designed for harsh, high vibration environments, the G3 Hammer Pump ideally handles high shock hammer/breaker applications with ease. With precision engineered pump elements based on our industry-leading G3 platform, this pump keeps up with the work you do, increasing both productivity and your bottom line.

SPIN-OFF RESERVOIR COVER Quickly fill hard to pump grease from the top of the reservoir. T **ROBUST COVER DESIGN** G3 Reinforced ribs to withstand high vibration and shock applications. Hamme Available in both 4 liter and 8 liter capacities. VERSATILE PUMP ELEMENTS **UP TO THREE PUMP ELEMENTS** POWER AND LOW LEVEL OPTIONS CPC or DIN-style connectors make for easy, no-hassle installations.

TYPICAL APPLICATIONS

- Hydraulic breakers/hammers
- Carrier or pedestal mounted



	96G278	133789	96G279	133791	
Power source	18-30 VDC; 2.5A current, 60W, inrush/locked rotor 6A				
Fluids handled	Chisel Paste, NLGI #000 to #2 Greases				
Operating temperature	-40°F to 158°F (-40°C to 70°C)				
Reservoir size	4 Liter		8 Liter		
Control option	Control pump via external control method				
Pump elements	Ships with one pump element, add up to two additional pump elements				
Output pressure	5,100 psi (35.1 MPa, 351.6 bar)				
Pump output	0.25 in ³ /min (4 cm ³ /min) per pump element				
Pump outlet	1/4-18 NPSF, Mates with 1/4-18 NPT male fittings				
Protection grade	IP69K				
Instruction Manual	332291				
	-			~	

Designed for You to Succeed

G3 24 VDC HYDRAULIC BREAKER/HAMMER CHISEL PASTE LUBRICATION PUMPS

	PART NUMBER	DESCRI
	966278	4 Liter, 5-Wire CPC Cable
	966279	8 Liter, 5-Wire CPC Cable
8	133789	4 Liter, External Low Level, 2 DIN Ca
Sec.	133791	8 Liter, External Low Level, 2 DIN Ca

ACCESSORIES

PART NUMBER	DESCRIPTION
26A910	4,000 psi kit (1/4 NPT to 1/8 NPT reducer bushing, 1/8 NPT tee-fitting, 4,
26C030	5,000 psi kit (1/4 NPT to 1/8 NPT reducer bushing, 1/8 NPT tee-fitting, 5,
571041	Replacement pump element
571063	Output union kit – 2 pump elements
571026	Output union kit – 3 pump elements
125910	G3 pump mounting L-bracket



MULTIPLE RESERVOIR OPTIONS

Built to withstand the harshest of greases, such as chisel paste and other greases containing additives.

0.25 in3/min (4 cm3/min) per element. 5,100 psi (351.6 bar).

PTION

4,000 psi pressure relief valve) 5,000 psi pressure relief valve)











Every Graco purchase comes with A+ Customer Service.

Questions? Call (800) 533-9655

For more information visit graco.com

©2022 Graco Inc. 353051 Rev. A 12/22 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. For more information on Graco's intellectual property, see www.graco.com/patent or www.graco.com/patent