



EGP™ TRANSFER AND EGP ON-DEMAND

Electric Convenience



PROVEN QUALITY. LEADING TECHNOLOGY.

EFFICIENT FLUID HANDLING

There's an easier, more efficient way to pump fluid to your critical equipment. Graco's all-electric EGP pumps reduce operating costs without compromising the durability you expect from the industry leader in pumping solutions. Add convenience and peace of mind to your everyday operations with our latest, most current innovation.

EGP TRANSFER PUMPS

Use the EGP Transfer Pump in locations where compressed air is unavailable or too cumbersome for short-distance fluid transfer.



ELECTRICAL FLEXIBILITY

Available in 12 VDC and 115 VAC power options.

SMOOTH FLUID FLOW 8 GPM (30 LPM)

When running the output of the pump does not pulsate but outputs a smooth and consistent flow.

HEAVY-DUTY MOTOR WITH LONG LIFE

Industrial-grade electric motors with over-temperature protection on 115 VAC models.

CONSISTENT PRESSURE

Built-in fluid bypass valve protects pump and downstream components.

PUMP PROTECTION

Includes inlet strainer to keep larger debris out of pump housing and extend pump life.

PLUG AND PLAY

Self-priming, precision-machined pump design.

TYPICAL APPLICATIONS

- Filling bulk tanks from drums
- Lubricant transfer from remote locations
- Construction equipment
- Agricultural equipment
- Filling in-plant machinery
- Evacuating used oil receivers
- Filling shop oil furnaces with new or used oil
- Automotive and truck service garages
- Fleet marine and personal boat service
- Aircraft maintenance

EGP ON-DEMAND PUMPS

Install the EGP On-Demand Pump in a variety of applications including workshops, mobile trucks and industrial plants. Use it as an energy-efficient option to standard pneumatic pumps.



ELECTRICAL FLEXIBILITY

Available in 12 VDC and 115 VAC power options.

SMOOTH FLUID FLOW 4 GPM (15 LPM)

When running the output of the pump does not pulsate but outputs a smooth and consistent flow.

HEAVY-DUTY MOTOR WITH LONG LIFE

Industrial-grade electric motor with over-temperature protection on 115 VAC model.

FLUID FLOW WHEN NEEDED

On-demand pressure sensing technology starts and stops the pump during the dispense.

PUMP RELIABILITY

Internal inlet and outlet checks keep pump section flooded to maintain prime for reliable performance.


SIMULTANEOUS DISPENSES

Pump long distances and supply fluid to multiple dispense points.


TYPICAL FLUIDS HANDLED

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Waste oil
- Antifreeze
- Hydraulic fluids
- Cutting oils
- Non-flammable oil-based solvents
- Oil-based herbicide carriers

EGP Transfer Pumps Performance Chart



EGP On-Demand Pumps Performance Chart



ORDERING INFORMATION

	EGP TRANSFER PUMP PACKAGES				EGP ON-DEMAND PUMP PACKAGES	
Package Part Number	25T819	25T820	25T822	—	—	—
Pump Part Number	—	—	—	25U346	25T817	25T818
Voltage	12 VDC	115 VAC	115 VAC	115 VAC	115 VAC	12 VDC
Hertz	—	60 Hz	60 Hz	60 Hz	60 Hz	—
Motor Type	TENV	ODP	ODP	TENV – IP55	TENV – IP55	TENV
Horsepower	1/2	1/2	3/4	1.0	1.5	3/4
Maximum Current (Amps)	30	8.7	9.9	9.1	14.4	60
Maximum Free Flow Rate gpm (lpm)	3.8 (14.4)	3.9 (14.8)	7.7 (29.1)	8.0 (30.3)	3.7 (14.0)	3.8 (14.4)
Maximum Pressure psi (bar)	65 (4.5)	65 (4.5)	65 (4.5)	120 (8.3)	500 (34.5)	325 (22.4)
Automatic Relief Setting psi (bar)	65 (4.5)	65 (4.5)	65 (4.5)	120 (8.3)	500 (34.5)	325 (22.4)
Inlet	1 in NPT	1 in NPT	1 in NPT	1 in NPT	3/4 in NPT	3/4 in NPT
Outlet	3/4 in NPT	3/4 in NPT	3/4 in NPT	3/4 in NPT	1/2 in NPT	1/2 in NPT
Bung Adapter	260061					
Dispense Kit	133376		—	—	—	—
Suction Kit	133375		—	—	—	—
Wetted Parts	Carbon steel with zinc plating, stainless steel, galvanized steel, aluminum, nitrile, rubber, PVC, PVC cement				Carbon steel with zinc plating, stainless steel, galvanized steel, aluminum, nitrile, rubber	
Weight lb (kg)	25 (11)	22 (10)	25 (11)	25 (11)	36 (16.3)	36 (16.3)
Manual	3A8569	3A8568	3A8568	3A8568	3A8570	3A8571



Every Graco purchase comes
with A+ Customer Service.

Questions?
Call (800) 533-9655

For more information visit graco.com