

DYNA-STAR® XT PUMPS

An Electric Alternative to Pneumatic Grease Pumps

Electrify your lubrication system with Dyna-Star XT, an electric lubrication pump with XT Motor technology. Designed for heavy-duty mining equipment and industrial applications, Dyna-Star XT offers a drop-in upgrade for pneumatic grease pumps.

BENEFITS

ELECTRIFIES THE LUBRICATION SYSTEM — NO AIR SUPPLY NEEDED

• Eliminates issues related to dirty air, icing or inconsistent output

XT MOTOR TECHNOLOGY LEADS TO EXTENDED LIFE AND OPTIMIZED OUTPUT

- Increased Torque: Up to 15x more torque than conventional motors
- · Consistent flow rate regardless of back pressure
- · Quieter performance provides a more comfortable working environment

SEAMLESS DROP-IN UPGRADES FOR EXISTING SYSTEMS

HIGHER LONG-TERM ROI

 Increased ease-of-repair compared to competitive pneumatic pumps in this size class

SPECIFICATIONS

Stoke	4.75 in (121 mm)
Operating Temperature	14°F to 104°F (-10°C to 40°C)
Control Options	PLC or GLC 4400 AC (Part #24B596 series "K" or later)
Max Working Pressure	7,000 psi (48.3 MPa, 483 bar)
Pump Output	2.1 in ³ (34.4 cm ³) / per cycle
Max Cycle Rate	30 cycles per minute
Pump Outlet	3/4 in NPT
Protection Grade	IP66, Type 4X
Electrical Ratings	100-120 V, Single Phase, 50/60 Hz, 12 A
Instruction Manual	X021555

DYNA-STAR XT	PART# 2009845
Dyna-Star XT Pump	
Motor Assembly Kit	2010688
Complete Pump Lower Assembly Kit	2010555
Pump Lower Seal Kit	2009432
Rotor Kit	2011184
Stator Cap Kit	2011185
Complete Rotor Repair Kit	2011186
Control Board Kit	2011187
Follower Plate - 400 lb (180 kg) Barrel	25U200
Drum Cover - 400 lb (180 kg) Barrel	25U202
Pump Flange Mounting Kit	2007333



For more information, visit graco.com