

# **Safety Data Sheet**

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

MSD025ENNZ Revision: A Issue Date: June 2023

# **Graco Fusion Grease**

# **Graco (Graco Australia)**

Chemwatch: **5350-37** Version No: **5.1** 

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

## Chemwatch Hazard Alert Code: 1

Issue Date: **06/02/2023** Print Date: **06/02/2023** L.GHS.NZL.EN.E

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier		
Product name	Graco Fusion Grease	
Chemical Name	Not Applicable	
Synonyms	Part Number: 118665, 248279	
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains zinc oxide and antimony diamyldithiocarbamate)	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Grease.
nelevant identified uses	Use according to manufacturer's directions.

## Details of the manufacturer or supplier of the safety data sheet

Registered company name	Graco (Graco Australia)	
Address	Suite 17, 2 Enterprise Drive Bundoora VIC 3083 Australia	
Telephone	+61 3 9468 8500	
Fax	+61 3 9468 8599	
Website	www.graco.com	
Email	ANZTA@graco.com	

# Emergency telephone number

Association / Organisation	Graco (Graco Australia)	
Emergency telephone numbers	+61 3 9468 8500 (Mon-Fri 8am-18pm),+61 467 836 080 (After Hours)	
Other emergency telephone numbers	Not Available	

## **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

Classification <sup>[1]</sup>	spiration Hazard Category 1, Serious Eye Damage/Eye Irritation Category 2, Hazardous to the Aquatic Environment Long-Term Hazard ategory 2	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria	6.1E (aspiration), 6.4A, 9.1B	

# Label elements

Hazard pictogram(s)







Signal word Da

Dangei

## Hazard statement(s)

H304	May be fatal if swallowed and enters airways.	
H319	Causes serious eye irritation.	
H411	Toxic to aquatic life with long lasting effects.	

# Precautionary statement(s) Prevention

P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.

Chemwatch: **5350-37** Version No: **5.1**  Page 2 of 12

**Graco Fusion Grease** 

Issue Date: **06/02/2023**Print Date: **06/02/2023** 

#### Precautionary statement(s) Response

P301+P310	SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.	
P331	NOT induce vomiting.	
P305+P351+P338	EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P391	Collect spillage.	

#### Precautionary statement(s) Storage

P405 Store locked up.

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

## **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
64742-52-5.	>60	naphthenic distillate, heavy, hydrotreated (severe)
64742-53-6.	30-40	naphthenic distillate, light, hydrotreated (severe)
1314-13-2	1-5	zinc oxide
15890-25-2	1-5	antimony diamyldithiocarbamate
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

#### **SECTION 4 First aid measures**

#### Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  Wash out immediately with water.  If irritation continues, seek medical attention.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.  If failure/misuse of high pressure/hydraulic equipment results in injection of grease/oil through the skin seek urgent medical attention. Treat as surgical emergency.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

**NOTE:** Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

## **SECTION 5 Firefighting measures**

## Extinguishing media

- Foam.
- Dry chemical powder.
- ► BCF (where regulations permit).
- ► Carbon dioxide.
- Water spray or fog Large fires only.

# Special hazards arising from the substrate or mixture

Fire Fighting

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

## Advice for firefighters

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.

Chemwatch: 5350-37 Page 3 of 12 Issue Date: 06/02/2023 Version No: 5.1 Print Date: 06/02/2023

## **Graco Fusion Grease**

	<ul> <li>Do not approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>May emit acrid smoke.</li> <li>Mists containing combustible materials may be explosive.</li> <li>Combustion products include:</li> <li>carbon dioxide (CO2)</li> <li>sulfur oxides (SOx)</li> <li>nitrogen oxides (NOx)</li> <li>metal oxides</li> <li>other pyrolysis products typical of burning organic material.</li> </ul>

## **SECTION 6 Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Methods and material for cont	3 · F
Minor Spills	Environmental hazard - contain spillage.  Slippery when spilt.  Clean up all spills immediately.  Avoid contact with skin and eyes.  Wear impervious gloves and safety goggles.  Trowel up/scrape up.  Place spilled material in clean, dry, sealed container.  Flush spill area with water.
Major Spills	Environmental hazard - contain spillage.  Slippery when spilt.  Minor hazard.  Clear area of personnel.  Alert Fire Brigade and tell them location and nature of hazard.  Control personal contact with the substance, by using protective equipment as required.  Prevent spillage from entering drains or water ways.  Contain spill with sand, earth or vermiculite.  Collect recoverable product into labelled containers for recycling.  Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.  Wash area and prevent runoff into drains or waterways.  If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

Precautions for safe handling	
Safe handling	<ul> <li>Limit all unnecessary personal contact.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>When handling DO NOT eat, drink or smoke.</li> <li>Always wash hands with soap and water after handling.</li> <li>Avoid physical damage to containers.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

## Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	CARE: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire. Oil leaks in a pressurized circuit may result in a fine flammable spray (the lower flammability limit for oil mist is reached for a concentration of about 45 g/m3 Autoignition temperatures may be significantly lower under particular conditions (slow oxidation on finely divided materials Avoid reaction with oxidising agents Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

Issue Date: **06/02/2023**Print Date: **06/02/2023** 

## **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

#### Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	naphthenic distillate, heavy, hydrotreated (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	(om) - Sampled by a method that does not collect vapour
New Zealand Workplace Exposure Standards (WES)	naphthenic distillate, light, hydrotreated (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	(om) - Sampled by a method that does not collect vapour
New Zealand Workplace Exposure Standards (WES)	zinc oxide	Zinc oxide	2 mg/m3	5 mg/m3	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	zinc oxide	Zinc oxide respirable dust	0.1 mg/m3	0.5 mg/m3	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	antimony diamyldithiocarbamate	Antimony and compounds, as Sb	0.5 mg/m3	Not Available	Not Available	Not Available

## **Emergency Limits**

Ingredient	TEEL-1	TEEL-2	TEEL-3
naphthenic distillate, heavy, hydrotreated (severe)	140 mg/m3	1,500 mg/m3	8,900 mg/m3
naphthenic distillate, light, hydrotreated (severe)	1,100 mg/m3	1,800 mg/m3	40,000 mg/m3
zinc oxide	10 mg/m3	15 mg/m3	2,500 mg/m3

Ingredient	Original IDLH	Revised IDLH
naphthenic distillate, heavy, hydrotreated (severe)	2,500 mg/m3	Not Available
naphthenic distillate, light, hydrotreated (severe)	2,500 mg/m3	Not Available
zinc oxide	500 mg/m3	Not Available
antimony diamyldithiocarbamate	50 mg/m3	Not Available

## MATERIAL DATA

NOTE L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. European Union (EU) List of harmonised classification and labelling hazardous substances, Table 3.1, Annex VI, Regulation (EC) No 1272/2008 (CLP) - up to the latest ATP

## **Exposure controls**

Exposure controls	
Appropriate engineering controls	General exhaust is adequate under normal operating conditions.
Personal protection	
Eye and face protection	<ul> <li>Safety glasses with side shields; or as required,</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul>
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> <li>Eye wash unit.</li> </ul>

#### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-

Issue Date: **06/02/2023**Print Date: **06/02/2023** 

up to 100 x ES - A-2 P2 A-PAPR-2 P2 ^

^ - Full-face

 $A(All \ classes) = Organic \ vapours, \ B \ AUS \ or \ B1 = Acid \ gasses, \ B2 = Acid \ gas \ or \ hydrogen \ cyanide(HCN), \ B3 = Acid \ gas \ or \ hydrogen \ cyanide(HCN), \ E = Sulfur \ dioxide(SO2), \ G = Agricultural \ chemicals, \ K = Ammonia(NH3), \ Hg = Mercury, \ NO = Oxides \ of \ nitrogen, \ MB = Methyl \ bromide, \ AX = Low \ boiling \ point \ organic \ compounds(below 65 \ degC)$ 

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## **SECTION 9 Physical and chemical properties**

## Information on basic physical and chemical properties

Appearance	Appearance Off-white, smooth odourless paste; does not mix with water.				
•					
Physical state	Non Slump Paste	Relative density (Water = 1)	0.95		
Odour	No Odour	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available		
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available		
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable		
Flash point (°C)	204.4 (COC)	Taste	Not Available		
Evaporation rate	Not Available	Explosive properties	Not Available		
Flammability	Not Applicable	Oxidising properties	Not Available		
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available		
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Applicable		
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available		
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable		
Vapour density (Air = 1)	Not Available	VOC g/L	Not Applicable		

## **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

### **SECTION 11 Toxicological information**

#### Information on toxicological effects

Information on toxicological ef	fects
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.  Inhalation hazard is increased at higher temperatures.  Inhalation of oil droplets/ aerosols may cause discomfort and may produce chemical pneumonitis.
Ingestion	Ingestion may result in nausea, abdominal irritation, pain and vomiting
Skin Contact	The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.  The material may accentuate any pre-existing dermatitis condition  Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.  Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Еуе	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Principal route of exposure is by skin contact; lesser exposures include inhalation of fumes from hot oils, oil mists or droplets. Prolonged contact with mineral oils carries with it the risk of skin conditions such as oil folliculitis, eczematous dermatitis, pigmentation of the face (melanosis) and warts on the sole of the foot (plantar warts). With highly refined mineral oils no appreciable systemic effects appear to result through skin

Chemwatch: **5350-37** Page **6** of **12**Version No: **5.1** 

#### Graco Fusion Grease

Issue Date: 06/02/2023 Print Date: 06/02/2023

absorption

Exposure to oil mists frequently elicits respiratory conditions, such as asthma; the provoking agent is probably an additive. High oil mist concentrations may produce lipoid pneumonia although clinical evidence is equivocal. In animals exposed to concentrations of 100 mg/m3 oil mist, for periods of 12 to 26 months, the activity of lung and serum alkaline phosphatase enzyme was raised; 5 mg/m3 oil mist did not produce this response. These enzyme changes are sensitive early indicators of lung damage. Workers exposed to vapours of mineral oil and kerosene for 5 to 35 years showed an increased prevalence of slight basal lung fibrosis.

	TOXICITY	IRRITATION	
Graco Fusion Grease	Dermal (Rabbit) LD50: >5000 mg/kg <sup>[2]</sup>	Not Available	
	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
aphthenic distillate, heavy,	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
hydrotreated (severe)	Inhalation(Rat) LC50: 2.18 mg/l4h <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
naphthenic distillate, light,	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
hydrotreated (severe)	Inhalation(Rat) LC50: 2.18 mg/l4h <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit) : 500 mg/24 h - mild	
zinc oxide	Inhalation(Rat) LC50: >1.79 mg/l4h <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
	Oral (Rat) LD50: >5000 mg/kg <sup>[1]</sup>	Skin (rabbit) : 500 mg/24 h- mild	
		Skin: no adverse effect observed (not irritating) $[1]$	
	TOXICITY	IRRITATION	
antimony diamyldithiocarbamate	Dermal (rabbit) LD50: >16000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
	Oral (Rat) LD50: >16400 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) $^{[1]}$	
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		

NAPHTHENIC DISTILL ATE

Exposure to the material may result in a possible risk of irreversible effects. The material may produce mutagenic effects in man. This concern is raised, generally, on the basis of

appropriate studies with similar materials using mammalian somatic cells in vivo. Such findings are often supported by positive results from in vitro mutagenicity studies.

Studies indicate that normal, branched and cyclic paraffins are absorbed from the mammalian gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent that iso- or cyclo-paraffins.

The major classes of hydrocarbons have been shown to be well absorbed by the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with dietary lipids. The dependence of hydrocarbon absorption on concomitant triglyceride digestion and absorption, is known as the "hydrocarbon continuum hypothesis", and asserts that a series of solubilising phases in the intestinal lumen, created by dietary triglycerides and their digestion products, afford hydrocarbons a route to the lipid phase of the intestinal absorptive cell (enterocyte) membrane. While some hydrocarbons may traverse the mucosal epithelium unmetabolised and appear as solutes in lipoprotein particles in intestinal lymph, there is evidence that most hydrocarbons partially separate from nutrient lipids and undergo metabolic transformation in the enterocyte. The enterocyte may play a major role in determining the proportion of an absorbed hydrocarbon that, by escaping initial biotransformation, becomes available for deposition in its unchanged form in peripheral tissues such as adipose tissue, or in the liver.

NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to

cellular DNA.

ZINC OXIDE

(SEVERE)

HEAVY, HYDROTREATED

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives;

- The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:
- The adverse effects of these materials are associated with undesirable components, and
   The levels of the undesirable components are inversely related to the degree of processing;
- $\cdot \ \text{Distillate base oils receiving the same degree or extent of processing will have similar toxicities};\\$
- The potential toxicity of residual base oils is independent of the degree of processing the oil receives.
- · The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.

The degree of refining influences the carcinogenic potential of the oils. Whereas mild acid / earth refining processes are inadequate to substantially reduce the carcinogenic potential of lubricant base oils, hydrotreatment and / or solvent extraction methods can yield oils with no carcinogenic potential.

Unrefined and mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential carcinogenic and mutagenic activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Mutagenicity and carcinogenicity testing of residual oils has been negative, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size.

Toxicity testing has consistently shown that lubricating base oils have low acute toxicities. Numerous tests have shown that a lubricating base oil s mutagenic and carcinogenic potential correlates with its 3-7 ring polycyclic aromatic compound (PAC) content, and the level of DMSO extractables (e.g. IP346 assay), both characteristics that are directly related to the degree/conditions of processing Skin irritating is not significant (CONCAWE) based on 14 tests on 10 CASs from the OLBO class (Other Lubricant Base Oils). Each study lasted

Graco Fusion Grease & NAPHTHENIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE) & NAPHTHENIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE)

Issue Date: **06/02/2023**Print Date: **06/02/2023** 

for 24 hours, a period of time 6 times longer than the duration recommended by the OECD method).

Eye irritation is not significant according to experimental data (CONCAWE studies) based on 9 "in vivo" tests on 7 CASs from the OLBO class(Other Lubricant Base Oils).

Sensitisation: The substance does not cause the sensitization of the respiratory tract or of the skin. (CONCAWE studies based on 14 tests on 11 CASs from the OLBO class(Other Lubricant Base Oils))

Germ cell mutagenicity: The tests performed within the 'in vivo" studies regarding gene mutation at mice micronuclei indicated negative results (CONCAWE studies. AMES tests had negative results in 7 studies performed on 4 CASs from the OLBO class(Other Lubricant Base Oils)). Reproduction toxicity: Reproduction / development toxicity monitoring according to OECD 421 or 422 methods. CONCAWE tests gave negative results in oral gavage studies. Pre-birth studies regarding toxicity in the unborn foetus development process showed a maternal LOAEL (Lowest Observed Adverse Effect Level) of 125 mg/kg body/day, based on dermal irritation and a NOAEL (No Observable Adverse Effect Level) of 2000 mg/kg body/day, which shows that the substance

is not toxic for reproduction.

STOT (toxicity on specific target organs) – repeated exposure: Studies with short term repeated doses (28-day test) on rabbit skin indicated the NOAEL value of 1000 mg/kg. NOAEL for inhalation, local effects > 280 mg/m3 and for systemic effects NOAEL > 980 mg/m3. Sub-chronic toxicity

90-day study Dermal: NOAEL > 2000 mg/kg (CONCAWE studies).

Repeat dose toxicity:

Oral

NOAEL for heavy paraffinic distillate aromatic extract could not be identified and is less than 125 mg/kg/day when administered orally. Inhalation

The NOAEL for lung changes associated with oil deposition in the lungs was 220 mg/m3. As no systemic toxicity was observed, the overall NOAEL for systemic effects was > 980 mg/m3.

Dermal

In a 90 day subchronic dermal study, the administration of Light paraffinic distillate solvent extract had an adverse effect on survivability, body weights, organ weights (particularly the liver and thymus), and variety of haematology and serum chemistry parameters in exposed animals. Histopathological changes which were treatment-related were most prominent in the adrenals, bone marrow, kidneys, liver, lymph nodes, skin, stomach, and thymus. Based on the results of this study, the NOAEL for the test material is less than 30 mg/kg/day. Toxicity to reproduction:

Mineral oil (a white mineral oil) caused no reproductive or developmental toxicity with 1 mL/kg/day (i.e., 1000 mg/kg/day) in an OECD 421 guideline study, but did cause mild to moderate skin irritation. Therefore, the reproductive/developmental NOAEL for this study is =1000 mg/kg/day and no LOAEL was determined.

Developmental toxicity, teratogenicity:

Heavy paraffinic distillate furfural extract produced maternal, reproductive and foetal toxicity. Maternal toxicity was exhibited as vaginal discharge (dose-related), body weight decrease, reduction in thymus weight and increase in liver weight (125 mg/kg/day and higher) and aberrant haematology and serum chemistry (125 and/or 500 mg/kg/day). Evidence of potential reproductive effects was shown by an increased number of dams with resorptions and intrauterine death. Distillate aromatic extract (DAE) was developmentally toxic regardless of exposure duration as indicated by increased resorptions and decreased foetal body weights. Furthermore, when exposures were increased to 1000 mg/kg/day and given only during gestation days 10 through 12, cleft palate and ossification delays were observed. Cleft palate was considered to indicate a potential teratogenic effect of DAE.

The following Oil Industry Note (OIN) has been applied: OIN 8 - The classifications as a reproductive toxicant category 2; H361d (Suspected of damaging the unborn child) and specific target organ toxicant category 1; H372 (Causes damage to organs through prolonged or repeated exposure) need not apply if the substance is not classified as carcinogenic

Toxicokinetics of lubricant base oils has been examined in rodents. Absorption of other lubricant base oils across the small intestine is related to carbon chain length; hydrocarbons with smaller chain length are more readily absorbed than hydrocarbons with a longer chain length. The majority of an oral dose of mineral hydrocarbon is not absorbed and is excreted unchanged in the faeces. Distribution of mineral hydrocarbons following absorption has been observed in liver, fat, kidney, brain and spleen. Excretion of absorbed mineral hydrocarbons occurs via the faeces and urine. Based on the pharmacokinetic parameters and disposition profiles, the data indicate inherent strain differences in the total systemic exposure (~4 fold greater systemic dose in F344 vs SD rats), rate of metabolism, and hepatic and lymph node retention of C26H52, which may be associated with the different strain sensitivities to the formation of liver granulomas and MLN histiocytosis.

Highly and Severely Refined Distillate Base Oils

Acute toxicity: Multiple studies of the acute toxicity of highly & severely refined base oils have been reported. Irrespective of the crude source or the method or extent of processing, the oral LD50s have been observed to be >5 g/kg (bw) and the dermal LD50s have ranged from >2 to >5g/kg (bw). The LC50 for inhalation toxicity ranged from 2.18 mg/l to> 4 mg/l.

When tested for skin and eye irritation, the materials have been reported as "non-irritating" to "moderately irritating" Testing in guinea pigs for sensitization has been negative

Repeat dose toxicity: . Several studies have been conducted with these oils. The weight of evidence from all available data on highly & severely refined base oils support the presumption that a distillate base oil s toxicity is inversely related to the degree of processing it receives. Adverse effects have been reported with even the most severely refined white oils - these appear to depend on animal species and/ or the peculiarities of the study.

- The granulomatous lesions induced by the oral administration of white oils are essentially foreign body responses. The lesions occur only in rats, of which the Fischer 344 strain is particularly sensitive,
- The testicular effects seen in rabbits after dermal administration of a highly to severely refined base oil were unique to a single study and may have been related to stress induced by skin irritation, and
- The accumulation of foamy macrophages in the alveolar spaces of rats exposed repeatedly via inhalation to high levels of highly to severely refined base oils is not unique to these oils, but would be seen after exposure to many water insoluble materials.

Reproductive and developmental toxicity: A highly refined base oil was used as the vehicle control in a one-generation reproduction study. The study was conducted according to the OECD Test Guideline 421. There was no effect on fertility and mating indices in either males or females. At necropsy, there were no consistent findings and organ weights and histopathology were considered normal by the study s authors. A single generation study in which a white mineral oil (a food/ drug grade severely refined base oil) was used as a vehicle control is reported. Two separate groups of pregnant rats were administered 5 ml/kg (bw)/day of the base oil via gavage, on days 6 through 19 of gestation. In one of the two base oil dose groups, three malformed foetuses were found among three litters The study authors considered these malformations to be minor and within the normal ranges for the strain of rat.

#### Genotoxicity

In vitro (mutagenicity): Several studies have reported the results of testing different base oils for mutagenicity using a modified Ames assay Base oils with no or low concentrations of 3-7 ring PACs had low mutagenicity indices.

In vivo (chromosomal aberrations): A total of seven base stocks were tested in male and female Sprague-Dawley rats using a bone marrow cytogenetics assay. The test materials were administered via gavage at dose levels ranging from 500 to 5000 mg/kg (bw). Dosing occurred for either a single day or for five consecutive days. None of the base oils produced a significant increase in aberrant cells.

Carcinogenicity: Highly & severely refined base oils are not carcinogens, when given either orally or dermally.

NAPHTHENIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE) & ANTIMONY DIAMYLDITHIOCARBAMATE

No significant acute toxicological data identified in literature search.

NAPHTHENIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE) & NAPHTHENIC DISTILLATE, LIGHT,

The substance is classified by IARC as Group 3: **NOT** classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. 
 Chemwatch: 5350-37
 Page 8 of 12
 Issue Date: 06/02/2023

 Version No: 5.1
 Print Date: 06/02/2023

# **Graco Fusion Grease**

HYDROTREATED (SEVERE)			
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	✓

Legend:

X − Data either not available or does not fill the criteria for classification
 y − Data available to make classification

## **SECTION 12 Ecological information**

## Toxicity

Graco Fusion Grease	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Availabl
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	ErC50	72h	Algae or other aquatic plants	>1000mg/l	1
naphthenic distillate, heavy, hydrotreated (severe)	NOEC(ECx)	504h	Crustacea	>1mg/l	1
nyurotreateu (severe)	EC50	96h	Algae or other aquatic plants	>1000mg/l	1
	EC50	48h	Crustacea	>1000mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
	ErC50	72h	Algae or other aquatic plants	>1000mg/l	1
naphthenic distillate, light, hydrotreated (severe)	NOEC(ECx)	504h	Crustacea	>1mg/l	1
nyurotreateu (severe)	EC50	96h	Algae or other aquatic plants	>1000mg/l	1
	EC50	48h	Crustacea	>1000mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1344h	Fish	19-110	7
	LC50	96h	Fish	0.112mg/l	2
zinc oxide	EC50	72h	Algae or other aquatic plants	0.036-0.049mg/l	4
	EC50	48h	Crustacea	0.105mg/l	2
	EC10(ECx)	168h	Algae or other aquatic plants	0.0025mg/l	2
	EC50	96h	Algae or other aquatic plants	0.3mg/l	2
antimony diamyldithiocarbamate	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Availab

Fish: >100 mg/l Invertebrates: >100 mg/l Aquatic plants: >100 mg/l Microorganism: >100 mg/l [Graco] Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DO NOT discharge into sewer or waterways.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

# Bioaccumulative potential

Ingredient	Bioaccumulation
zinc oxide	LOW (BCF = 217)

# Mobility in soil

Ingredient	Mobility	
	No Data available for all ingredients	

## **SECTION 13 Disposal considerations**

## Waste treatment methods

Issue Date: **06/02/2023**Print Date: **06/02/2023** 

Product / Packaging disposal

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- ▶ Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

#### **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

#### **SECTION 14 Transport information**

# Labels Required



#### **Marine Pollutant**



HAZCHEM

2Z

#### Land transport (UN)

Zana tranoport (Ort)				
UN number	3077			
UN proper shipping name	NVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains zinc oxide and antimony diamyldithiocarbamate)			
Transport hazard class(es)	Class 9 Subrisk Not Applicable			
Packing group	III			
Environmental hazard	Environmentally hazardous			
Special precautions for user	Special provisions 274; 331; 335; 375  Limited quantity 5 kg			

## Air transport (ICAO-IATA / DGR)

UN number	3077					
UN proper shipping name	Environmentally hazardo	Environmentally hazardous substance, solid, n.o.s. (contains zinc oxide and antimony diamyldithiocarbamate)				
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	AO / IATA Subrisk Not Applicable				
Packing group	III	III				
Environmental hazard	Environmentally hazardous					
Special precautions for user	Special provisions  Cargo Only Packing Instructions  Cargo Only Maximum Qty / Pack  Passenger and Cargo Packing Instructions  Passenger and Cargo Maximum Qty / Pack  Passenger and Cargo Limited Quantity Packing Instructions  Passenger and Cargo Limited Maximum Qty / Pack		A97 A158 A179 A197 A215 956 400 kg 956 400 kg Y956 30 kg G			

# Sea transport (IMDG-Code / GGVSee)

UN number	3077		
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains zinc oxide and antimony diamyldithiocarbamate)		
Transport hazard class(es)	IMDG Class IMDG Subrisk	9 Not Applicable	
Packing group	III		

Version No: 5.1

## **Graco Fusion Grease**

Issue Date: **06/02/2023**Print Date: **06/02/2023** 

Environmental hazard	Marine Pollutant	
	EMS Number	F-A, S-F
Special precautions for user	Special provisions	274 335 966 967 969
	Limited Quantities	5 kg

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
naphthenic distillate, heavy, hydrotreated (severe)	Not Available
naphthenic distillate, light, hydrotreated (severe)	Not Available
zinc oxide	Not Available
antimony diamyldithiocarbamate	Not Available

## Transport in bulk in accordance with the ICG Code

Product name	Ship Type
naphthenic distillate, heavy, hydrotreated (severe)	Not Available
naphthenic distillate, light, hydrotreated (severe)	Not Available
zinc oxide	Not Available
antimony diamyldithiocarbamate	Not Available

# **SECTION 15 Regulatory information**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2020	
HSR002530	Cleaning Products Subsidiary Hazard Group Standard 2020	
HSR002535	Gases under Pressure Mixtures Subsidiary Hazard Group Standard 2020	
HSR002503	Additives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020	
HSR002606	Lubricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020	
HSR002612	Metal Industry Products Subsidiary Hazard Group Standard 2020	
HSR002624	N.O.S. Subsidiary Hazard Group Standard 2020	
HSR002638	Photographic Chemicals Subsidiary Hazard Group Standard 2020	
HSR002644	Polymers Subsidiary Hazard Group Standard 2020	
HSR002647	Reagent Kits Group Standard 2020	
HSR002648	Refining Catalysts Group Standard 2020	
HSR002653	Solvents Subsidiary Hazard Group Standard 2020	
HSR002670	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020	
HSR002684	Water Treatment Chemicals Subsidiary Hazard Group Standard 2020	
HSR100425	Pharmaceutical Active Ingredients Group Standard 2020	
HSR002600	Leather and Textile Products Subsidiary Hazard Group Standard 2020	
HSR002544	Construction Products Subsidiary Hazard Group Standard 2020	
HSR002549	Corrosion Inhibitors Subsidiary Hazard Group Standard 2020	
HSR002552	Cosmetic Products Group Standard 2020	
HSR002558	Dental Products Subsidiary Hazard Group Standard 2020	
HSR002565	Embalming Products Subsidiary Hazard Group Standard 2020	
HSR002571	Fertilisers Subsidiary Hazard Group Standard 2020	
HSR002573	Fire Fighting Chemicals Group Standard 2021	
HSR002578	Food Additives and Fragrance Materials Subsidiary Hazard Group Standard 2020	
HSR002585	Fuel Additives Subsidiary Hazard Group Standard 2020	
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2020	
HSR100580	Tattoo and Permanent Makeup Substances Group Standard 2020	
HSR100757	Veterinary Medicines Limited Pack Size Finished Dose Group Standard 2020	
HSR100758	Veterinary Medicines Non dispersive Closed System Application Group Standard 2020	
HSR100759	Veterinary Medicines Non dispersive Open System Application Group Standard 2020	

Issue Date: **06/02/2023**Print Date: **06/02/2023** 

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

#### naphthenic distillate, heavy, hydrotreated (severe) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List International Agency for Research on Cancer (IARC) - Agents Classified by the IARC

Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

## naphthenic distillate, light, hydrotreated (severe) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC

Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

## zinc oxide is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

antimony diamyldithiocarbamate is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

New Zealand Workplace Exposure Standards (WES)

#### **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

#### **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

#### Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

## **Tracking Requirements**

Not Applicable

## **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (naphthenic distillate, heavy, hydrotreated (severe); naphthenic distillate, light, hydrotreated (severe); antimony diamyldithiocarbamate)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (naphthenic distillate, light, hydrotreated (severe); antimony diamyldithiocarbamate)	
Vietnam - NCI	No (antimony diamyldithiocarbamate)	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

## **SECTION 16 Other information**

Revision Date	06/02/2023
Initial Date	09/05/2019

Page 12 of 12 Issue Date: 06/02/2023

Graco Fusion Grease Print Date: 06/02/2023

#### **SDS Version Summary**

Version	Date of Update	Sections Updated		
4.1	23/12/2022	Classification review due to GHS Revision change.		
5.1	06/02/2023	Appearance, Classification, Use		

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

## This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.