

Flow Meters

For Proportioning Equipment



For those in search of precision flow measurement

- Highest quality Flow Meters offered as a part of our Modular designed Electronic Proportioning Equipment
- Very accurate gear and mass flow meters, even with low flow rates.
- Ideal for finishing applications using most solventborne and waterborne paints and resins

For more information, visit our website at www.graco.com

PROVEN QUALITY. LEADING TECHNOLOGY.



Flow Meters

G250/G250 HR, G3000/G3000 HR and S3000

- Positive displacement, spur gear flow meter
- Designed for non-abrasive and unfilled materials
- Highly accurate, even with low flow rates
- Stainless steel compatible to handle low to medium viscosity materials
- ETL us, ATEX- and CE-marked

HG6000/HG6000 HR

- Positive displacement, helical gear flow meter
- Designed for higher flow rates and higher viscosity materials
- Highly accurate, even with low flow rates
- Stainless steel, water-base compatible for medium to high viscosity materials
- ATEX- and CE-marked

Coriolis Mass Flow

- Non-intrusive mass flow meter
- Designed for all abrasive and filled materials
- Stainless steel, waterborne and acid compatible for a wide range of materials
- Uses less material to flush
- Wide range of flow rates and material
- FM-, CSA- and ATEX-marked
- ATEX- and CE-marked
- 1/8 in and 3/8 in ID options

GRACO N.V. Industrieterrein Oude Bunders
Slakweidestraat 31 • B-3630 Maasmechelen
Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777
E-mail: info@graco.be • http://www.graco.com

©2010 Graco Inc. Form No. 336165 Rev. D 08/10. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

	G250	G250HR	G3000	G3000HR	S3000
Part number	249426	249427	239716 289813 (90° Sensor)	244292 289814 (90° Sensor)	258718
Maximum working fluid pressure	17 bar (1.7 MPa,250 psi)	17 bar (1.7 MPa,250 psi)	276 bar (28 Mpa,4000 psi)	276 bar (28 Mpa,4000 psi)	207 bar (20 MPa,3000 psi)
Flow range	75 - 3,800 cc/min	38 - 1,900 cc/min	75 - 3,800 cc/min	38 - 1,900 cc/min	50 - 2,000 cc/min
Viscosity range	20 - 3,000 cps	20 - 3,000 cps	20 - 3,000 cps	20 - 3,000 cps	0.5 - 1,000 cps
Resolution	0.119 cc/pulse	0.061 cc/pulse	0.119 cc/pulse	0.061 cc/pulse	0.021 cc/pulse
Material compatibility	Solventborne paints and resins (low solids), oil and catalysts	Solventborne paints and resins (low solids), oil and catalysts	Solventborne paints and resins (low solids), oil and catalysts	Solventborne paints and resins (low solids), oil and catalysts	Solvents, solventborne paints (no filled materials), oil and catalysts
Wetted parts	303 SST, tungsten carbide and PTFE	303 SST, tungsten carbide and PTFE	303 SST, tungsten carbide and PTFE	303 SST, tungsten carbide and PTFE	303 SST and PTFE
Recommended uses	Most commonly used flow meter in finishing applications. Uses include solventborne polyurethanes and epoxies	Low flow version of G3000. Flow rates as low as 50 cc/min	Most commonly used flow meter in finishing applications. Uses include solventborne polyurethanes and epoxies	Low flow version of G3000. Flow rates as low as 50 cc/min	Solvent tracking and metering of low viscosity materials
Instruction manuals	308778	308778	308778	308778	308778

	HG6000	HG6000HR	Coriolis Mass Flow	Coriolis Mass Flow
Part number	280560	246652	15T633* (1/8" ID)	15T634** (3/8" ID)
Maximum working fluid pressure	410 bar (41 MPa,6000 psi)	410 bar (41 MPa,6000 psi)	158 bar (16 MPa,2300 psi)	158 bar (16 MPa,2300 psi)
Flow range	50 - 22,700 cc/min	25 - 7,571 cc/min	20 - 3,800 cc/min	20 - 3,800 cc/min
Viscosity range	30 - 1,000,000 cps	30 - 1,000,000 cps	0.1 - 3,000 cps	0.1 - 3,000 cps
Resolution	0.286 cc/pulse	0.143 cc/pulse	0.061 cc/pulse, adjustable	0.061 cc/pulse, adjustable
Material compatibility	Solventborne and waterborne paints and resins, oil and catalysts	Solventborne paints and resins, oil and catalysts	Solventborne and waterborne materials, catalyzed varnishes and oil	Solventborne and waterborne materials, catalyzed varnishes and oil
Wetted parts	303 SST, tungsten carbide, and PTFE	303 SST, tungsten carbide, and PTFE	303 and 440 SST and PTFE	303 and 440 SST and PTFE
Recommended uses	Use with viscosities up to 100,000 cps and when flow rates exceed 4000 cc/min	Low flow version of G3000. Flow rates as low as 50 cc/min	Use with virtually any material and flow rate. Non intrusive design. Common uses include waterborne and acid-based materials	High flow version of 15D135
Instruction manuals	309834	309834	310696	310696

* ProMix 2KS Meter Kit Part Number 15V806 - 258150 - 313599 - 313599

** ProMix 2KS Meter Kit Part Number 258151